

California Department of Corrections



Uniform Specification Handbook

Revised : January 2003

UNIFORM SPECIFICATION HANDBOOK

TABLE OF CONTENTS

Policy, Purpose, Disclaimer.....	1
Employees.....	2
Non-Uniform Employees.....	2-3
Class 'A' Uniform – Male.....	3
Class 'A' Battle Jacket.....	4-5
Captains Coat.....	6-7
Class 'A' Trouser – Male.....	8-9
Class 'A' Shirts – Male.....	10-14
Class 'A' Uniform – Female.....	14-15
Class 'A' Blazer Jacket – Female.....	15-16
Class 'A' Shirts – Female.....	17-21
Class 'A' Line Skirt.....	22
Class 'A' Trouser – Female.....	22-24
Class 'A' Hat.....	24
Class 'B' Shirts – Male.....	24-29
Class 'B' Trouser – Male.....	29-31
Class 'B' Cargo Pant – Male.....	32-34
Class 'B' Shirts – Female.....	34-39
Class 'B' Trouser – Female.....	39-41
Class 'B' Cargo Pant – Female.....	42-44
Class 'B' Non-Water Proof Jacket.....	44-46
Class 'B' Non-Water Proof $\frac{3}{4}$ Length Jacket.....	47-50
Class 'B' Water Proof Foul Weather Jacket.....	50-55
Class 'B' Lightweight Jacket and Optional Lining.....	56
Class 'B' Hats – Ball Cap, Trooper Hat, Campaign Hat.....	57
Jumpsuits.....	58-59
Rain Gear.....	60

Table of contents

Continued

Sweater / Maternity Uniform.....	61
Security Squad / Escape Detail Uniform.....	62
Transportation Uniform.....	62-63
Funeral Uniform.....	63
Honor Guard Uniform / Accessories.....	64-65
Honor Guard Accouterments.....	66
Honor Guard Members/Equip/Weapons/Ammo.....	67-69
S.E.R.T Uniforms.....	69
Custody - Hat, Cap, Tie Requirements.....	69-70
Fire Service Uniform.....	70-79
Uniform Accessories/Departmental Awards.....	80-81
Hat Shields.....	81
Departmental Shoulder Emblems.....	82-83
Nameplate.....	84
Service Stripes	84
Maltese Cross	85
Rank Insignia	85
Sleeve Chevron (Sgt), Regulation Tie.....	86
Official Belt Buckle	86
Regulation Shoes.....	87
Miscellaneous Accessories for Uniform Staff.....	87-88
Departmental Badges.....	88-96
Medical Technical Assistant Uniform.....	96-99
Food Service Uniforms.....	99-100
Protective Vests.....	100-105
References.....	105

POLICY

All designated personnel shall wear regulation uniforms or work clothing and insignia as prescribed by the Director of the California Department of Corrections (CDC). Consistent design specifications for individual uniform garments shall be incorporated and distributed as a standardized statewide document, and shall henceforth be referred to as the "CDC Uniform Specification Handbook." Items not specifically addressed herein as associated with the CDC Department Operations Manual (DOM) Section 33020, or the CDC Uniform Specification Handbook, are considered unauthorized unless written authorization is obtained from the appropriate division's Deputy Director or their designee.

While on duty, employees shall dress in neat and conservative attire appropriate to their assignments. Employees shall not wear CDC uniforms in any tavern, gambling hall or nightclub, except if necessary in the performance of assigned duties.

PURPOSE

This section establishes uniform and/or dress requirements inclusive of the official insignia for the following classifications:

All custodial personnel inclusive of and below the rank of Correctional Captain.

- Fire department personnel.
- Medical personnel.
- Food services personnel.
- Craft and maintenance personnel.

DISCLAIMER

If any provision in this section is in conflict with a Memorandum of Understanding (MOU), the MOU shall prevail as it relates to the specific represented group.

EMPLOYEES

All uniform personnel shall:

- Purchase and maintain all required uniforms, accessories, and equipment except items specifically exempted by this section and/or the appropriate MOU.
- Furnish their own collar insignia, shoulder insignia, sleeve chevrons, shoulder patches, hat shield and other required uniform equipment.
- Maintain their uniform and approved equipment in clean, neat serviceable condition.
- Wear the uniform in a manner that displays a professional approach to their assignment and is representative of the prestige of the Department.
- Keep in mind that individual actions reflect on the entire Department as they represent the Department in the public view.

Uniformed employees, when dressed in uniform, whether on duty or off duty, are subject to public scrutiny and shall not:

- Purchase or drink alcoholic beverages in public.
- Participate in political activities.
- Engaging in selling or soliciting.
- Engage in any other action or behavior which reasonable persons would deem inappropriate for a uniformed peace officer.

NONUNIFORM EMPLOYEES

Employees not required to wear a uniform shall wear neat and conservative clothing in keeping with the requirements of their assignments. Employees' personal hygiene is to reflect cleanliness. Clothing is to be neat, in good repair and fit properly in order to project a professional and positive image.

Fingernails shall be neat, well trimmed and enhance a professional image. Fingernail length and polish shall be appropriate for the specific assignment and/or task being performed.

Hair shall be styled in a fashion, which will not impair vision or create a safety hazard in the work area. Beards, moustaches and hair should be clean and neatly trimmed.

Jewelry should be kept to a minimum and should enhance a professional image. There will be no jewels, ornaments, or rings/studs worn on the visible facial areas other than the ear.

Blue denim clothing or clothing similar to that worn by inmates shall not be worn. Wardens shall establish and enforce local dress codes and personal grooming standards.

REGULATION UNIFORM – CUSTODY

Regulation custody uniforms shall be as specified in DOM Section 33020. Individual garment specifications are addressed within this CDC Uniform Specification Handbook.

OFFICIAL CLASS “A” UNIFORM – MALE

The below-specified uniform shall be worn by male correctional captains, facility captains, correctional lieutenants, correctional sergeants and correctional officers:

- Regulation battle jacket with insignia (dress jacket).
- Regulation trousers - Forest green with 1/2-inch black and gold piping.
- Black leather belt 1-1/2-inch or 1-3/4-inch width with single gold metal prong tongue buckle, buckle shall be no wider than 2 x 2 inches (no decorations except official Department belt buckle or warden approved institutional belt buckle).
- Black clip-on or Velcro fastened tie.
- Black socks (solid color).
- Regulation uniform hat with gold insignia and gold chin-strap.
- Regulation short or long sleeve shirt.
- Black plain-toe shoes or boots conservatively designed without buckle.
- Regulation departmental badge.

- Departmental shoulder patch attached to the sleeves of regulation shirt and regulation dress jacket.
- Departmental nameplate (white letters on black plate).
- Tie bar or tie tack (gold in color).
- Whistle (gold in color).
- Identification card.
- Raincoat (when applicable).

CLASS "A" BATTLE JACKET

FABRIC

Raeford Mills #8247, Style #96912, 55% Dacron Polyester/45% Worsted Washable Wool.

14 oz. per linear yard. Serge weave. Forest Green.

DESIGN

The jacket shall be mid-length with zipper front to the semi peak lapels. Coat construction shall be used throughout with body and sleeves being fully lined.

BODY DETAIL

The front shall be plain with patch pockets with flaps. The front facings shall be of self goods a minimum of 3" wide. There shall be a badge tab and epaulets. The back shall be two piece, bi-swing style with a one piece self-belt 2" wide. There shall be a pointed, handmade take up tab on each side with one button. Since there is no waistband, the bottom of the jacket shall be finished with a minimum 2-1/2" turn up sewn to the lining so that no outside stitches show. The jacket shall have shoulder pads and arm shields.

SLEEVES

The sleeves shall be regular coat style, set in with a single needle machine. They shall have a minimum 2" hem.

POCKETS

There shall be two outside pleated patch pockets, rounded at the lower corners, approximately 5" wide x 6" deep on size 42 and down. On size 44 and up, the patch pocket will measure approximately 5-5/8" wide and 6-1/4" deep. The flaps shall be

scalloped and measure 5-3/4" wide and 3" long at the center and at each side. They shall have velcro closures on each side to hold down flap. There shall be one cut-in inside pocket on the right.

COLLAR

The collar shall be interlined with Pellon. The under collar shall be of the same fabric as the top collar.

BRAID

One-half inch gold on black background (A.H. Rice #2914, Color 1) nyla-twist braid, sewn on the top of each sleeve from seam to seam, 3 inches above the cuff.

ZIPPER

The jacket shall close with a YKK #5 brass, separating zipper. The color of the zipper tape shall be compatible with that of the outer goods.

EPAULETS

The epaulets shall be made of self goods. They shall be sewn into the sleeve head seam, x stitched, and tacked to the jacket at the neck.

BUTTONS

There shall be 24 Ligne Gold Eureka buttons on the pocket flaps, epaulets, and take-up tab. The pocket flap buttons shall be toggle type and the others sew-on type.

THREAD

All sewing is to be done with Polyester core thread or 100 percent Spun Polyester thread.

SIZE TAG AND CARE INSTRUCTIONS

Each jacket shall have a sewn in label giving care instructions and shall be marked with lot number, size, fiber content and WPL number.

FINISHING AND PRESSING

All loose threads shall be removed. Each jacket shall be pressed and shaped properly.

WARRANTY

One year against workmanship or fabric defects.

CORRECTIONAL CAPTAIN COAT

FABRIC

Outer Goods: Raeford Mills #8247, Style #96912, 55% Dacron Polyester/45% Worsted Washable Wool. 14 oz. per linear yard. Serge weave. Forest Green.

Lining: Rayon Satin. Color Fast and treated to resist perspiration.

DESIGN

Semi-form fitting model blouse with notch lapels, four button front with epaulets. Single breasted. Coat construction shall be used throughout. Body and sleeves are to be fully lined.

BODY DETAIL

The blouse shall be plain style front. There shall be a badge tab, four false pockets with scalloped flaps. It shall have a fused front and a separate fused chest piece. Only a high quality woven fusible hair canvas will be acceptable. Fusing shall be done on a tray feed or belt driven fusing press to insure proper bonding. The inside facing shall be made of the same goods as the outer fabric. The front buttonholes must be cut first type. There shall be a two piece back; two side panels with vents 12 inches long closed with Velcro or zippers. The shoulders are to have pads. The arm holes are to have sweat shields made of outer fabric, piped with rayon to be securely set under each arm over the lining. The top sleeve linings shall be machine felled to the body.

SLEEVES

The sleeves shall be regular coat style, set in with single needle having a minimum 2" hem. The bottom of the sleeves shall be lined.

POCKETS

There shall be four false pockets with scalloped flaps. The upper flaps to be 5-1/2" wide and lower flaps 8" wide with both flaps being 2-1/2" deep. Corners to be sewn down. There shall be two inside cut-in pockets, approximately 6" wide and 6" deep.

BRAID

One-half inch gold on black background (A. H. Rice #2914, Color 1) nyla-twist braid, sewn on the top of each sleeve from seam to seam 3" above the cuff.

OUTLETS

All body seams to have outlets of not less than 3/4". Turn up at sleeve to be not less than 2-1/2".

COLLAR

The collar shall not be over 1-7/8" wide in back when finished but shall be lined with high quality collar canvas. The under collar is to be made of all wool or pre-padded under collar cloth.

EPAULETS

Epaulets shall be made of outer goods. They shall be sewn into the sleeve seams, X-stitched, and fastened with 24 ligne gold Eureka metal buttons toggled to the blouse at the edge of the collar.

BADGE TAB

The badge tab shall be made of outer fabric 1-1/2" wide by 2-1/4" long, with 2 metal eyelets spaced vertically 1-1/2" apart. It is to be centered approximately 1/2" above the upper left pocket flap.

BUTTONS

There shall be sewn to the front of the blouse four - 36 Ligne Gold Eureka metal buttons secured with stay buttons. The pocket flaps and epaulets shall be secured with 24 ligne gold Eureka metal shank buttons.

THREAD

All sewing is to be done with Polyester core thread or 100 percent Spun Polyester thread.

SIZE TAG AND CARE INSTRUCTIONS

Each jacket shall have a sewn in label giving care instructions and shall be marked with lot number, size, fiber content and WPL number.

FINISHING AND PRESSING

All loose threads shall be removed. Each jacket shall be pressed and shaped properly.

WARRANTY: One year against workmanship or fabric defects.

CLASS "A" TROUSER - MALE

FABRIC

Raeford Mills #8247, Style # 96912, 55% Dacron Polyester/45% Worsted Washable Wool. 14 oz. per linear yard. Serge weave. Forest Green.

DESIGN

Shall be made on a uniform pattern, having a plain front with straight side pockets and two back pockets.

POCKETS

The side pockets shall have a minimum opening of 6-1/2" and they shall be approximately 5" from the bottom of the opening. They will be stitched, turned, and restitched. The inside front pocket facing shall be a separate piece of self material finishing no less than 1-1/4" wide. The back pockets will have a minimum opening of 5-1/2" wide and will be 6" deep. They shall be made with a Reese PW automatic machine and finished on the outside with an exposed top and bottom cord. Each back pocket shall have a button through pocket flap to close. The side pockets shall have straight bartacks and the back pockets are to be bartacked with a triangular bartacking machine (straight bartacks will be accepted).

POCKETING

All pocketing shall be black, 75% Polyester/25% Cotton with a minimum thread count of 86 x 56. The weight shall be 3.0 yds/lb.

WAISTBAND

The waistband shall be 2" wide and shall be closed with a crush-proof hook and eye, the eye being bartacked for stability. The waistband curtain, attached with a rocap machine, will have Snugtex and be made of black, 75% Polyester/25% Cotton. No roll waistband stiffener, 3/4" in width, shall be sewn into the waistband on the front of the trouser from side seam to side seam. The trousers are to be made with a continuous closed waistband. The waistband shall be set on and shall be stitched below the lower edge through the outer fabric and the waistband curtain.

INSIDE TRIM

The right fly lining and crotch lining will be the same fabric and color as the waistband curtain and shall be sewn to the left fly below the zipper. A separate french fly made of the outer fabric shall be sewn to the inside right fly.

BELT LOOPS

There shall be a minimum of 5 keystone style belt loops on waist sizes 28, 29, 30, and a minimum of 7 on all sizes over 30. Each loop is to be approximately 1-3/4" wide at the top and 1-1/2" at the bottom. Except for the back loop which shall be 3/4" wide and tacked on, all loops will be sewn into the bottom of the waistband and into the rocap. They shall accommodate a 1-5/8" belt.

BRAID

One-half inch gold on black background (A. H. Rice #2914, Color 1) nyla-twist braid on the pant. The braid shall extend from the bottom of waistband to the bottom of the pant leg.

ZIPPER

The trousers shall be closed with a YKK #45 brass zipper and have a brass bottom stop at the base of the zipper chain. A straight bartack will be sewn through from the outside of the garment to the inside at the bottom of the fly. It shall be sewn through the zipper tape; the right and left fly and the right fly lining. The right and left fly shall be joined by an additional bartack located below the bottom zipper stop on the inside of the trouser.

CREASING

The front and rear crease in the trouser legs must incorporate a permanent modified silicone crease produced by the "Lintrak System".

SEAMING

The entire trouser is to be seamed with Polyester core thread. The seat seam shall be stitched with a tandem needle seat seaming machine.

SIZE TAG AND CARE INSTRUCTIONS

The trouser shall have a sewn in label giving care instructions, and an outside waistband label which will be marked with lot number, size, fiber content and WPL number. A permanent size label shall be sewn inside on the hip pocket. Trouser shall bear the following guarantee label: "This garment is manufactured of 55% Polyester / 45% Wool, CDC / CYA Approved".

FINISHING AND PRESSING

All loose threads shall be removed. Trousers must be pressed completely and properly with the side seam, inseam, and seat seam pressed open. There must be a Texpak clip attached to the top fly of the finished trousers.

WARRANTY

One year against workmanship or fabric defects.

CLASS "A" LONG SLEEVE SHIRT - MALE

FABRIC

Content: 55% Dacron Polyester/45% Worsted Wool. Tropical weave conforming to the following specifications:

Weight: 8 - 8-1/2 oz. per linear yard.

Construction: 60 ends per inch. 50 picks per inch.

Tensile: 100 lbs. warp. 80 lbs. filling.

COLOR

California Department of Corrections Tan

STYLE

Form fitting, plain front coat style with banded collar and long sleeves with barrel cuffs. Two plain breast pockets with scalloped flaps. Shoulder straps. Exterior badge piece. Matching inside yoke and collar band of high lustre Poly Twill.

COLLAR & STAND

Collar points to measure 3-1/4" long with fused-in Mylar stays. Collar height at rear 1-1/2". One quarter inch double needle topstitched. Collar stand to measure 1-5/16" at rear. Collar and band to be die cut. Band interlined with "Crease N Tack". Collar interlined with stabilized Mellopress #285.

FRONT

The left front shall have a top center 1-3/4" wide with four rows of stitches 7/8" apart. The shirt will have seven buttons and buttonholes on the front; spacing between each will be 3-3/4" except the spacing between the neck button and the first button on the front, which will be 3-1/4". The fronts shall be joined to the yoke so that both raw edges of the yoke are turned under, with the front sandwiched between, then all three are stitched down with a 1/16" raised stitch. Safety stitch joining unacceptable. Top center interlined with stabilized Mellopress #550.

SHOULDER STRAPS

Asymmetrical shape 1/4" double needle topstitched to be set on yoke with leading topstitch conforming with front joining seam. To measure 2" at sleeve tapering to 1-3/8" and set not more than 1/2" from folded collar. Creased and edge stitched shoulder strap construction unacceptable.

BADGE REINFORCEMENT

Exterior badge piece to finish 1-1/8" wide by 2-1/4" long with two tan metal eyelets spaced 1-1/4" apart with bottom eyelet centered 1-1/2" above left flap.

POCKETS

Two plain breast pockets with rounded corners. Pocket to measure 6" wide, 6" deep. Left breast pocket to have 1-1/2" pencil stitch. Each pocket to have Velcro fasteners 3/4" long by 1/2" wide, positioned on both edges of pocket to correspond with outer scalloped flap points.

FLAPS

Deep scalloped design to measure 6-1/4" across, 2-3/4" in depth at center point and 2-1/2" at sides. Secured to shirt front approximately 1/4" above pocket. Left flap to have invisible pencil opening 1-1/2" to correspond precisely with pencil slot of pocket. Both flaps to be interlined with stabilized Mellopress #550. Creased and edge stitched pocket flap construction unacceptable. Underside of flap to have Velcro fasteners 3/4" long by 1/2" wide positioned on outer points of both pocket flaps.

SLEEVES AND CUFFS

Long sleeves cut straight and whole with 5-1/2" sleeve vent. Sleeve shall have a one piece elbow reinforcement and vent facing. Elbow reinforcement shall extend into the sleeve closing seam. Lower facing shall measure approximately 1/2" in width. Cuff to measure 3" with rounded corners. There shall be two buttons with corresponding buttonholes on each cuff and one button and buttonhole in the sleeve facing. Cuffs to be 1/4" double needle topstitched and interlined with stabilized Mellopress #550.

MILITARY CREASES

Five silicone sharp military creases on all shirts. One crease on each front to be centered vertically through pockets and flaps. Spacing for military creases on shirt back to be proportionate to the size of the shirt as follows:

Sizes 14 through 15-1/2" - creases to be 4-3/4" apart

Sizes 16 through 18 inclusive - creases to be 5-3/4" apart as measured from the center of the crease.

BUTTONS

First grade 22 ligne melamine to match.

STITCHING

Entire shirt to be double stitched 1/4" apart.

THREAD

All sewing threads to be fast color polyester core polyester wrap to match.

CONSTRUCTION

Collars and flaps are made by the conventional construction. Top ply, bottom ply and interlining are first stitched together, then turned rightside out and finally topstitched.

COUNTRY OF MANUFACTURE

All raw materials and assembly thereof made in the U.S.A.

CLASS "A" SHORT SLEEVE SHIRT – MALE

FABRIC

Content: 55% Dacron Polyester/45% Worsted Wool. Tropical weave conforming to the following specifications:

Weight: 8 - 8-1/2 oz. per linear yard.

Construction: 60 ends per inch. 50 picks per inch.

Tensile: 100 lbs. warp. 80 lbs. filling.

COLOR

California Department of Corrections Tan

STYLE

Form fitting, plain front coat style with convertible collar and short sleeves. Two plain breast pockets with scalloped flaps. Shoulder straps. Exterior badge piece. Matching inside yoke and banana band of high lustre Poly Twill.

COLLAR

Convertible collar shall be one piece and measure 3-1/4" long at points with fused in Mylar stays. One quarter inch double needle topstitched. Collar to be interlined with stabilized Mellopress #285.

FRONT

Each front shall have a facing 3" in width. The left front shall have a top center 1-1/2" wide with four rows of stitches 7/8" apart. Stitching on top center is not to be visible on the turn-back facing. The shirt will have seven buttons and buttonholes on the front; spacing between each will be 3-3/4" except the spacing between the neck button and the first button on the front, which will be 2-1/2". The fronts shall be joined to the yoke so that both raw edges of the yoke are turned under, with the front sandwiched between, then all three are stitched down with a 1/16" raised stitch. Safety stitch joining unacceptable. Top center interlined with stabilized Mellopress #550.

SHOULDER STRAPS

Asymmetrical shape 1/4" double needle topstitched to be set on yoke, with leading topstitch conforming with front joining seam. To measure 2" at sleeve tapering to 1-3/8" and set not more than 1/2" from folded collar. Creased and edge stitched shoulder strap construction unacceptable.

BADGE REINFORCEMENT

Exterior badge piece to finish 1-1/8" wide by 2-1/4" long with two tan metal eyelets spaced 1-1/4" apart with bottom eyelet centered 1-1/2" above left flap.

POCKETS

Two plain breast pockets with rounded corners. Pocket to measure 6" wide, 6" deep. Left breast pocket to have 1-1/2" pencil stitch. Each pocket to have Velcro fasteners 3/4" long by 1/2" wide positioned on both edges of pocket to correspond with outer scalloped flap points.

FLAPS

Deep scalloped design to measure 6-1/4" across, 2-3/4" in depth at center point and 2-1/2" at sides. Secured to shirt front approximately 1/4" above pocket. Left flap to have invisible pencil opening 1-1/2" to correspond precisely with pencil slot of pocket. Both flaps to be interlined with stabilized Mellopress #550. Creased and edge stitched pocket flap construction unacceptable. Underside of flap to have Velcro fasteners 3/4" long by 1/2" wide positioned on outer points of both pocket flaps.

SHORT SLEEVES

Sleeves are to be straight and whole, to have 3/4" hem and to finish approximately 9" long from shoulder seam.

MILITARY CREASES

Five silicone sharp military creases on all shirts. One crease on each front to be centered vertically through pockets and flaps. Spacing for military creases on shirt back to be proportionate to the size of the shirt as follows:

Sizes 14 through 15-1/2" - creases to be 4-3/4" apart.

Sizes 16 through 18 inclusive - creases to be 5-3/4" apart as measured from the center of the crease.

BUTTONS

First grade 22 ligne melamine to match.

STITCHING

Entire shirt to be double stitched 1/4" apart.

THREAD

All sewing threads to be fast color polyester core polyester wrap to match.

CONSTRUCTION

Collars and flaps are made by the conventional construction. Top ply, bottom ply and interlining are first stitched together, then turned rightside out and finally topstitched.

COUNTRY OF MANUFACTURE

All raw materials and assembly thereof made in the U.S.A.

OFFICIAL CLASS ""A" UNIFORM – FEMALE

The below-specified uniform shall be worn by female correctional captains, correctional lieutenants, correctional sergeants and correctional officers:

- Regulation dress female jacket, blazer style with insignia, or the regulation dress battle jacket with insignia, or the optional facility captain coat.
- Regulation skirt or pants - Forest green with 1/2-inch black and gold piping. (Pants only shall have the piping).

- Black leather belt 1-1/2 inch or 1-3/4 inch width with single gold prong tongue buckle, buckle shall be no wider than 2 x 2 inches (no decorations except official Department belt buckle or warden approved institutional belt buckle).
- Black clip-on or Velcro fastened tie, or criss-cross tie.
- Seamless hose (flesh color) with skirt only; black socks (solid in color) with slacks.
- Regulation uniform hat with gold insignia and gold chin strap.
- Regulation short or long sleeve shirt; dry clean only.
- Black plain-toe shoes or boots conservatively designed without buckles.
- Regulation departmental badge.
- Departmental shoulder patch attached to the sleeves of regulation shirt and regulation dress jacket.
- Departmental nameplate (white letters on black plate).
- Tie bar or tie tack (gold in color).
- Whistle (gold in color).
- Identification card.
- Raincoat (when applicable).

CLASS "A" BLAZER STYLE DRESS JACKET – FEMALE

RaeFord Mills #8247, Style 96912U55% Dacron Polyester/45% Worsted Wool. Serge weave. Forest Green. Restora Finish.

DESIGN

Blazer style jacket, single breasted, with a drop notch lapel, deep arm holes, side seam vents for access to duty belt, lower welt pockets, inside pocket, and badge tab. Front bust darts to extend into welt pockets and side seam. Lap over open vent. Jacket to be fully lined with 100 percent acetate.

SLEEVES

The top and bottom to be two piece coat style sleeve. Sleeve head. Arm tape.

POCKETS

There shall be two lower welt pockets. The welt is to be approximately 1" and the width of the pocket is to be 5-1/2". The pocket depth is approximately 7". There shall be one inside pocket 4" wide by 4" deep.

BUTTONS

There shall be two 36 Ligne Gilt Eureka front buttons for closure.

SIDE VENTS

There shall be 2 side vents measuring 8" long with 1-1/4" overlapping to the front. The overlap is to have a self fabric facing.

EPAULETS

The epaulets shall be 4" long; 1-1/2" wide made of self goods. They shall be sewn into the sleeve head seem, x-stitched, and fastened with 24 Ligne gold Eureka metal buttons at the edge of the collar.

BACK

Four piece back.

CHEST

Fused front construction.

BADGE TAB

The badge tab shall be made of outer fabric 1-1/2" wide by 2-1/4" long, with two metal eyelets spaced vertically 1-1/2" apart, placed on the left chest.

BRAID

One-half inch gold on black background (A. H. Rice #2914, Color 1) nyla-twist braid, sewn at the top of each sleeve from seam to seam, 3" above the cuff.

SHOULDER EMBLEMS

There shall be a California Department of Corrections emblem sewn into each shoulder centered approximately 1" down from the shoulder seam. Emblems are to be provided by the California Department of Corrections.

FINISHING AND PRESSING

All loose threads shall be removed. Each jacket shall be pressed and shaped properly.

SIZE TAG AND CARE INSTRUCTIONS

Each jacket shall have a sewn in label giving care instructions and shall be marked with a lot number, size, fiber content, and WPL number.

WARRANTY

One year against workmanship or fabric defects.

CLASS "A" LONG SLEEVE SHIRT- FEMALE

FABRIC

Content: 55% Dacron Polyester/45% Worsted Wool. Tropical weave conforming to the following specifications:

Weight: 8 - 8-1/2 oz. per linear yard.

Construction: 60 ends per inch. 50 picks per inch.

Tensile: 100 lbs. warp. 80 lbs. filling.

COLOR

California Department of Corrections Tan

STYLE

Shirt shall be made in a form fitting coat style with banded collar and long sleeves with barrel cuffs. Two plain breast pockets with scalloped flaps. Shoulder straps. Exterior badge piece. Matching inside yoke and collar band of high lustre Poly Twill.

COLLAR & STAND

Collar points to measure 3-1/16" long with fused-in Mylar stays. Collar height at rear 1-1/2". One quarter inch double needle topstitched. Collar stand to measure 1-5/16" at rear. Collar and band to be die cut. Band interlined with "Crease N Tack". Collar interlined with stabilized Mellopress #285.

FRONT

The right front shall have a top center 1-1/2" wide with four rows of stitches 7/8" apart. The right front shall have six buttonholes spaced 3-1/4" apart and set 3/4" from edge. The left front shall have a button stay hem of self goods approximately 7/8" wide with six 22 Ligne melamine buttons. Top center interlined with stabilized Mellopress #550. The fronts shall be joined to the yoke so that both raw edges of the yoke are turned under,

with the front sandwiched between, then all three are stitched down with a 1/16" raised stitch. Safety stitch joining unacceptable.

BACK (OPTIONAL)

The back to have a 1-1/8" inverted box pleat in center from yoke seam to waist with a triangular stitch at the waist. Pleat to be stitched closed from the triangular bartack to bottom hem.

SHOULDER STRAPS

Asymmetrical shape 1/4" double needle topstitched to be set on yoke, with leading topstitch conforming with front joining seam. To measure 2" at sleeve tapering to 1-3/8" and set not more than 1/2" from folded collar. Creased and edge stitched shoulder strap construction unacceptable.

BADGE REINFORCEMENT

Exterior badge piece to finish 1-1/8" wide by 2-1/4" long with two tan metal eyelets spaced 1-1/4" apart with bottom eyelet centered 1-1/2" above left flap.

POCKETS

Two plain breast pockets with rounded corners. Pocket to measure 5" wide, 5" deep. Both breast pockets to have 1-1/2" pencil stitch. Each pocket to have Velcro fasteners 3/4" long by 1/2" wide positioned on both edges of pocket to correspond with outer scalloped flap points.

FLAPS

Deep scalloped design to measure 5-1/4" across, 2-1/4" in depth at center point and 1-3/4" at sides. Secured to shirt front approximately 1/4" above pocket. Both flaps to have invisible pencil opening 1-1/2" to correspond precisely with pencil slot of pocket. Both flaps to be interlined with stabilized Mellopress #550. Creased and edge stitched pocket flap construction unacceptable. Underside of flap to have Velcro fasteners, 3/4" long by 1/2" wide positioned on outer points of both pocket flaps.

SLEEVES AND CUFFS

Long sleeves cut straight and whole with 3-3/4" sleeve vent. Sleeve shall have a one piece elbow reinforcement and vent facing. Elbow reinforcement shall extend into the sleeve closing seam. Lower facing shall measure approximately 1/2" in width. Cuff to measure

2-1/2" with rounded corners. There shall be a two button adjustable cuff. Cuffs to be 1/4" double needle topstitched and interlined with stabilized Mellopress #550.

MILITARY CREASES

Five silicone sharp military creases on all shirts. One crease on each front to be centered vertically through pockets and flaps. Spacing for military creases on shirt back to be proportionate to the size of the shirt.

BUTTONS

First grade 22 Ligne melamine to match.

STITCHING

Entire shirt to be double stitched 1/4" apart.

THREAD

All sewing threads to be fast color polyester core polyester wrap to match.

CONSTRUCTION

Collars and flaps are made by the conventional construction. Top ply, bottom ply and interlining are first stitched together, then turned rightside out and finally topstitched.

COUNTRY OF MANUFACTURE

All raw materials and assembly thereof made in the U.S.A.

CLASS "A" SHORT SLEEVE SHIRT – FEMALE

FABRIC

Content: 55% Dacron Polyester/45% Worsted Wool. Tropical weave conforming to the following specifications:

Weight: 8 - 8-1/2" oz. per linear yard.

Construction: 60 ends per inch. 50 picks per inch.

Tensile: 100 lbs. warp. 80 lbs. filling.

COLOR

California Department of Corrections Tan

STYLE

Shirt shall be made in a form fitting coat style with convertible collar and short sleeves. Two plain breast pockets with scalloped flaps. Shoulder straps. Exterior badge piece. Matching inside yoke and banana band of high lustre Poly Twill.

COLLAR & STAND

Convertible collar shall be one piece and measure 2-7/8" long at points with fused in Mylar stays. One quarter inch double needle topstitched. Collar to be interlined with stabilized Mellopress #285.

FRONT

The right front shall have a top center 1-1/2" wide with four rows of stitches 7/8" apart. Stitching on The top center is not to be visible on the turn-back facing. The shirt will have seven buttons and buttonholes on the front; spacing between each will be 3-1/4" except the spacing between the neck button and the first button on the front, which will be 2-1/2". The fronts shall be joined to the yoke so that both raw edges of the yoke are turned under, with the front sandwiched between, then all three are stitched down with a 1/16" raised stitch. Safety stitch joining unacceptable. Top center interlined with stabilized Mellopress #550.

BACK (OPTIONAL)

The back to have a 1-1/8" inverted box pleat in center from yoke seam to waist with a triangular stitch at the waist. Pleat to be stitched closed from the triangular bartack to bottom hem.

SHOULDER STRAPS

Asymmetrical shape 1/4" double needle topstitched, to be set on yoke with leading topstitch conforming with front joining seam. To measure 2" at sleeve tapering to 1-3/8" and set not more than 1/2" from folded collar. Creased and edge stitched shoulder strap construction unacceptable.

BADGE REINFORCEMENT

Exterior badge piece to finish 1-1/8" wide by 2-1/4" long with two tan metal eyelets spaced 1-1/4" apart with bottom eyelet centered 1-1/2" above left flap.

POCKETS

Two plain breast pockets with rounded corners. Pocket to measure 5" wide, 5" deep. Both breast pockets to have 1-1/2" pencil stitch. Each pocket to have Velcro fasteners 3/4" long by 1/2" wide positioned on both edges of pocket to correspond with outer scalloped flap points as sample.

FLAPS

Deep scalloped design to measure 5-1/4" across, 2-1/4" in depth at center point and 1-3/4" at sides. Secured to shirt front approximately 1/4" above pocket. Both flaps to have invisible pencil opening 1-1/2" to correspond precisely with pencil slot of pocket. both flaps to be interlined with stabilized Mellopress #550. Creased and edge stitched pocket flap construction unacceptable. Underside of flap to have Velcro fasteners, 3/4" long by 1/2" wide positioned on outer points of both pocket flaps as sample.

SHORT SLEEVES

Sleeves are to be straight and whole, to have 3/4" hem and to finish approximately 8-1/2" long from shoulder seam.

MILITARY CREASES

Five silicone sharp military creases on all shirts. One crease on each front to be centered vertically through pockets and flaps. Spacing for military creases on shirt back to be proportionate to the size of the shirt.

BUTTONS

First grade 22 Ligne melamine to match.

STITCHING

Entire shirt to be double stitched 1/4" apart.

THREAD

All sewing threads to be fast color polyester core polyester wrap to match.

CONSTRUCTION

Collars and flaps are made by the conventional construction. Top ply, bottom ply and interlining are first stitched together, then turned rightside out and finally topstitched.

COUNTRY OF MANUFACTURE

All raw materials and assembly thereof made in the U.S.A.

CLASS "A" LINE SKIRT

The "A" Line Skirt specifications shall be as follows:

- Material: Forest green, 55% Dacron Polyester / 45% Worsted Washable Wool.
- Modified "A" line, 2-gore front, 2-gore back--2/3 lined; smooth waist-to-hip fit (no darts); left side seam zipper opening; five, 3/4-inch self material belt loops; 1-5/8 inch finished width self fabric waistband; hook and eye or button and buttonhole belt band closure (optional); and inside tape hanger loops.
- Vertical openings on pockets at left and right seam; one watch pocket on right side waistline; and matching lining (The employee may decide to omit the pockets if she wishes).
- Two-inch hem turned-under; edge pinked or taped (optional).
- Eight-inch metal side zipper with automatic lock.

Shall be worn no higher than the top of the kneecap.

CLASS "A" TROUSER – FEMALE

FABRIC

Raeford Mills #8247, Style #96912, 55% Dacron Polyester/45% Worsted Washable Wool. 14 oz. per linear yard. Serge weave. Forest Green.

DESIGN

Shall be made on a modified ladies uniform pattern with a plain front, straight side pockets, two back pockets and an elastic back.

POCKETS

The front pocket opening will be a minimum 5-1/2" and be 5" deep from the bottom of the opening. They will be stitched, turned, and restitched. The inside front pocket facing shall be a separate piece of self material finishing no less than 1-1/4" wide. The back pockets will have a minimum opening of 5-1/2" wide and will be 6" deep on size 14 and up. On size 12 and down, the minimum opening will be 5" wide and 6" deep. They shall be made with a Reese PW automatic machine and finished on the outside with an exposed top and bottom cord. The front pocket will have straight bartacks; the back pockets shall be bartacked with a triangular bartacking machine (straight bartacks will be accepted).

POCKETING

All pocketing shall be black, 75% Polyester/25% Cotton with a minimum thread count of 86 x 56. The weight shall be 3.0 yds/lb.

WAISTBAND

The waistband shall be 2" wide and shall be closed with a crush-proof hook and eye, the eye being bartacked for stability. The waistband curtain, attached with a rocap machine, will have Snugtex and be made of black, 75% Polyester/25% Cotton. No roll waistband stiffener, 3/4" in width, shall be sewn into the waistband on the front of the trouser from side seam to side seam. The trousers are to be made with a continuous closed waistband. There shall be a special elastic back using the closed covered method. The waistband shall be set on and shall be stitched below the lower edge through the outer fabric and the waistband curtain.

INSIDE TRIM

The right fly lining and crotch lining will be the same fabric and color as the waistband curtain. The right fly lining shall be sewn to the left fly below the zipper.

BELT LOOPS

There shall be a minimum of 5 belt loops on waist sizes 12 and down and a minimum of 7 on all sizes 14 and over. Each loop is to be approximately 1-3/4" wide at the top and 1-1/2" at the bottom. Except for the back loop which shall be 3/4" wide and tacked on, all loops will be sewn into the bottom of the waistband and into the rocap. They shall accommodate a 1-5/8" belt.

BRAID

One-half inch gold on black background (A. H. Rice #2914, Color 1) nyla-twist braid sewn on the trouser. The braid shall extend from the bottom of waistband to the bottom of the trouser leg.

ZIPPER

The trousers shall be closed with a YKK #45 brass zipper and have a brass bottom stop at the base of the zipper chain. A straight bartack will be sewn through from the outside of the garment to the inside at the bottom of the fly. It shall be sewn through the zipper tape; the right and left fly and the right fly lining. The right and left fly shall be joined by an additional bartack located below the bottom zipper stop on the inside of the trouser.

CREASING

The front and rear crease in the trouser legs must incorporate a permanent modified silicone crease produced by the "Lintrak System".

SEAMING

The entire trouser is to be seamed with Polyester core thread. The seat seam shall be stitched with a tandem needle seat seaming machine.

SIZE TAG AND CARE INSTRUCTIONS

The trouser shall have a sewn in label giving care instructions, and an outside waistband label which will be marked with lot number, size, fiber content and WPL number. A permanent size label shall be sewn inside on the hip pocket. Trouser shall bear the following guarantee label: "This garment is manufactured of 55% Polyester/45% Wool, CDC/CYA Approved".

FINISHING AND PRESSING

All loose threads shall be removed. Trousers must be pressed completely and properly with the side seam, inseam, and seat seam pressed open. There must be a Texpak clip attached to the top fly of the finished trousers.

WARRANTY

One year against workmanship or fabric defects.

CLASS "A" UNIFORM HAT

All on-duty uniformed custody personnel will be required to wear the class "A" uniform hat on any official business where a Class "A" Uniform is required for off grounds duties.

For staff who are required to wear a Class "A" Uniform for duties on grounds, or who voluntarily choose to wear a Class "A" Uniform, the Class "A" Hat is optional. However, the Class "A" Hat must be available to the on duty staff member.

OFFICIAL CLASS "B" UNIFORM

CLASS "B" LONG SLEEVE SHIRT – MALE

FABRIC

Content: All synthetic tropical weave, 65% Dacron Polyester/35% Avril Rayon conforming to the following specifications:

Weight: 6.6 oz./yd. 2

Construction: 49 warp X 36 filling yarns per square inch. All yarns size 10/1 singles.

Air Permeability: Ft. 3/Min./Ft. 2 131 ASTM D 737-46
Tensile: Break Strength 105 warp - 90 filling (lbs.)
Pilling: Minimum 4.9 rating

COLOR

Silvertan matching standard sample on display.

STYLE

Plain front coat style, form-fitting, collar attached, long sleeves with barrel cuffs. Two plain breast pockets. Shoulder straps. Metal eyelet badge reinforcement. Matching inside yoke and collarband of high luster Rayon.

COLLAR & STAND

Style and dimensions as sample on display. Collar points to measure 3-1/4" long with fused-in Mylar stays. Collar height at rear 1-1/2". Collar stand to measure 1-5/16" at rear and band to be died cut and interlined with stabilized Mellopress (#285 in collar, "Crease N Tack" in band.

FRONT

The left front shall have a top center 1-1/2" wide with two double rows of stitches. The shirt will have / buttons and buttonholes on the front, spacing between each will be 3-3/4". Top center interlined with Mellopress #550.

SHOULDER STRAPS

Style and Dimensions as sample. Asymmetrical shape double topstitched, to be set on yoke with leading topstitch conforming with front joining seam. To measure 2" at sleeve tapering to 1-3/8" and set not more than 1/2" from folded collar. Cross Stitched approximately 2" from sleeve seam. Creased and edge stitched shoulder strap construction unacceptable.

BADGE REINFORCEMENT

Exterior holder to finish 1-1/8" wide by 2-1/4" deep, with two metal eyelets spaced 1-1/8" apart with button eyelet centered 1-1/2" above left flap.

POCKETS

Two plain breast pockets. Pocket to measure 5-5/8" wide, 6" deep. Left breast pocket to have 1-1/2" pencil stitch. Each pocket to have Velcro fasteners 3/4" long by 1/2" wide positioned on both edges of pocket to correspond with outer scalloped flap points as sample.

FLAPS

Deep scalloped design to measure 6-1/4" across, 2-3/4" in depth at center point and 2-1/2" at sides. Secured to shirt front approximately 1/4" above pocket. Left flap to have invisible pencil opening 1-1/2" to correspond precisely with pencil slot of pocket. Both flaps to be interlined with stabilized Mellopress #550. Creased and edge stitched pocket flap construction unacceptable. Underside of flap to have Velcro tape 3/4" long by 1/2" wide positioned on outer points of both pocket flaps as sample.

SLEEVES AND CUFFS

To be long sleeves cut straight and whole with 5-1/2" sleeve vent. Sleeve shall have a one-piece round elbow reinforcement and vent facing. Elbow reinforcement shall extend into the sleeve, closing seam. Lower facing shall measure approximately 1/2" in width. Cuff to measure 3" with rounded corners. There shall be two buttons with corresponding buttonholes on each cuff and one button and buttonhole in the sleeve facing.

MILITARY CREASES

Seven baked in sharp military creases on all shirts. One crease on each front to be centered vertically through pockets and flaps. Spacing for military creases on shirt back to be proportionate to the size of the shirt as follows:

Sizes 14 through 15-1/2" - creases to be 4-3/4" apart

Sizes 16 through 18 inclusive - creases to be 5-3/4" apart as measured from the center of the crease.

BUTTONS

First grade 22 ligne melamine to match.

STITCHING

All parts double topstitched, collar, flaps, pockets, cuffs, straps, top center, double elbows, yoke, side close and sleeve inserting.

THREAD

All sewing threads to be fast color polyester core polyester wrap to match.

CONSTRUCTION

Collars, flaps, and shoulder straps are made by the conventional construction. Top ply, bottom ply and interlining are first stitched together, then turned rightside out and finally topstitched.

COUNTRY OF MANUFACTURE

All raw materials and assembly thereof made in the U.S.A.

CLASS "B" SHORT SLEEVE SHIRT – MALE

FABRIC

Content: All synthetic tropical weave; 65% Dacron Polyester, 35% Avril Rayon, conforming to the following specifications:

Weight:	6.6 oz./yd. 2
Construction:	49 warp X 36 filling yarns per square inch. All yarns size 10/1 singles.
Air Permeability:	Ft. 3/Min./Ft. 2 131 ASTM D 737-46
Tensile:	Break Strength 105 warp - 90 filling (lbs.)
Properties:	Tear Strength 9.7 warp - 8.5 filling (lbs.)
Pilling:	Minimum 4.9 rating

COLOR

Silvertan matching standard sample on display.

STYLE

The style shall be known as a convertible collar, short sleeve, and coat shirt, with full-length tail and form-fitting. The shirt to have two outside breast pockets and scalloped flaps having one button each. Also to have full badge sling and shoulder straps. The back to have a double yoke, with high luster polyester/cotton poplin band and yoke trim.

COLLAR

Convertible collar shall be one piece and measure 3-1/4" long at points. The collar shall be made with permanent collar stays. Collar to be topstitched 1/4" off the edge. To be interlined with #285 Mellopress.

FRONT

The left front shall have a top center 1-1/2" wide with two double rows of stitches. The shirt will have seven buttons and buttonholes on the front, spacing between each will be 3-3/4". Top center to be interlined with #550 Mellopress.

SHOULDER STRAPS

Style and dimensions as sample. Asymmetrical shape, topstitched 1/4" off the edge to be set on yoke with leading topstitch conforming with front joining seam. To measure 2" at sleeve tapering to 1-3/8" set not more than 1/2" from folded collar. Cross stitched

approximately 2" from sleeve seam. Crossed and edge stitched shoulder strap construction unacceptable.

BADGE REINFORCEMENT

Exterior holder to finish 1-1/8" wide by 2-1/4" deep, with two metal eyelets spaced 1-1/8" apart with button eyelet centered 1-1/2" above left flap.

POCKETS

Two plain breast pockets. Pockets to measure 5-5/8" wide, 6" deep. Left breast pocket to have 1-1/2" pencil stitch. Each pocket to have Velcro tape 3/4" long by 1/2" wide, positioned on both edges of pocket to correspond with outer scalloped flap points as sample.

FLAPS

Deep scalloped design to measure 6-1/4" across, 2-3/4" in depth at center point, and 2-1/2" at sides. Secured to shirt front approximately 1/4" above pocket. Left flap to have invisible pencil opening 1-1/2" to correspond precisely with pencil slot of pocket. Both flaps to be interlined with #550 Mellopress. Creased and edge stitched pocket flap construction unacceptable.

Underside of the flap to have Velcro tape 3/4" long by 1/2" wide positioned on outer points of both pocket flaps as sample.

SHORT SLEEVES

Sleeves are to be straight and whole, to have 3/4" hem, and to finish approximately 9" long from shoulder seam.

MILITARY CREASES

Seven baked-in sharp military creases on all shirts. One crease on each front to be centered vertically through pockets and flaps. Spacing for military creases on shirt back to be proportionate to the size of the shirt as follows:

Sizes 14 through 15-1/2" - creases to be 4-3/4" apart

Sizes 16 through 18 inclusive - creases to be 5-3/8" apart as measured from the center of the crease.

BUTTONS

First grade 22 ligne melamine to match.

STITCHING

Single needle throughout. All topstitched 1/4" off the edge. Sleeve inserting and side close felling, safety stitched.

THREAD

All sewing threads to be fast color polyester core polyester wrap to match.

CONSTRUCTION

Collars, flaps and shoulder straps are made by the conventional construction. Top ply, bottom ply and interlining are first stitched together, then turned rightside out and finally topstitched.

COUNTRY OF MANUFACTURE

All raw materials and assembly thereof made in the U.S.A.

CLASS "B" TROUSER – MALE

FABRIC

65% Dacron Polyester/35% Rayon. Oz/Linear Yard (60" width). Post Cured Fabric Weight: 13 - 13 1/2. Tensile Strength: 145 Lbs. Warp/65 Lbs. fill. Tear Strength: 2,000 Grams Warp & Fill. Gabardine weave. Forest Green.

DESIGN

Trouser shall be manufactured from a men's uniform trouser pattern. The trouser styling shall incorporate a plain front, two quarter top front pockets, and two hip pockets. Trouser is to be straight leg style.

POCKETS

The two front pockets will be quarter top style with an opening of 6" and a depth of 5-3/4", measured from the bottom of the opening. Front pockets shall have straight bartacks (use of triangle bartacks will be cause for rejection) at the top and bottom of pocket openings. Pockets shall be constructed using the stitch, turn, and topstitch method. Pocket facings shall be made of the basic fabric and must measure a minimum of 3" in width at the top.

The two hip pockets shall have a minimum opening of 5-1/2" and a minimum depth of 5-3/4", measured from the bottom of the pocket opening. Hip pockets shall be constructed using the double welt method on a REECE PW Machine. The welts shall be finished in such a manner that there is no topstitching (topstitched hip pocket welts shall be cause for rejection). The corners of the hip pocket openings shall have firm

straight bartacks for reinforcement (triangle bartacks are unacceptable). Hip pocket facings are to be made of basic fabric and have a minimum depth of 3/4". The left hip pocket shall have a centered tab made of basic cloth inserted into the top welt with bartacks at the top and bottom of the tab to form an opening for a button. A button shall be located below the bottom welt corresponding in location with the tab.

The watch pocket shall be located on the right front at the waistband. This pocket shall have a minimum opening and depth of 2-3/4". The front of the pocket shall be made of pocketing fabric. The back of the pocket shall be made of basic fabric, and the two pieces are securely stitched together. Each corner of the pocket opening shall have firm straight bartacks.

POCKETING

The pocketing shall be 70% polyester/30% cotton, 2.9 oz. per square yard (60" width) with a minimum 78 x 64 count. Pocketing must have a durable press finish and the color of the pocketing must be black.

WAISTBAND

The trouser will be made with a stretch waistband system, which is designed to provide the wearer with a more comfortable and better fitting trouser. The waistband shall be constructed using a "closed method" and shall measure 2" wide when finished. The waistband closure shall be accomplished with a crush proof hook and eye. The hook and eye shall be reinforced with stays made of a non-woven fabric that are anchored by the topstitching for the fly facing and curtain. This topstitching must be to the top of the waistband. The waistband must be topstitched 1/16" below the waistband seam for added strength. The top portion of the inside of the waistband is to consist of the same fabric as used for pocketing (70% polyester, 30% cotton - minimum 80 X 62 (+/-) 2 count). The fabric is to be cut on the bias for maximum comfort. To be 1-3/4" wide and to finish 1-1/8" wide after construction.

Upper waistband curtain to be inner lined with stretch Ban-Rol canvas. This canvas fabric consists of a warp of 47 ends of texturized nylon and a fill of 34 ends of 750 denier polyester monofilament. The woven fabric is coated with latex, which completely encapsulates all yarns. This finish canvas fabric weighs 12.0 oz/yd². The canvas will be cut 1-3/8" monofilaments running vertically and have a 10% stretch.

The bottom portion of the waistband curtain will be a blend of 32% nylon, 38% polyester, 18% rubber (3 strands) 11% lycra and 1% acrylic woven 1-7/8" wide and to finish a minimum 1- 5/8" wide. To have a minimum of 40% stretch characteristics.

NOTE: In a performance stretch waistband, the upper and lower portion of the band will perform different functions.

The upper portion should allow a comfort fit at the waist when bending or sitting and must maintain a crisp, clean appearance at the outer waistband. This part of the band will stretch 10% and be firm enough to prevent waistband rollover.

The bottom portion of the waistband stretches over the hip to give support to the lower back and abdomen. In addition, this high stretch portion of the band should constantly be pressed up by the hips, preventing the slack from slipping down while being worn, even if heavy keys, change, or other items are carried in the pockets or on the belt. The three rubberized strands ensure that shirts stay tucked in for neat appearance.

FLY

Trouser shall have a metal memory lock zipper. There shall be a French Fly tab closure on the inside of the right fly. The tab shall be double ply made of the basic cloth (tabs made of pocketing material or a “grown on” French Fly will be cause for rejection). The right fly shall be lined with the same fabric as the waistband curtain and pocketing. The fly lining shall be sewn to the left fly below the zipper in a neat and durable manner. A button shall be located on the left fly corresponding with the French Fly tab to provide a clean and comfortable closure. There shall be a firm straight bartack at the bottom of the fly going through the zipper.

BELT LOOPS

There shall be a minimum of seven belt loops 3/4” in width of double thickness. Each loop must have a non-woven interlining. All loops (except for the back center loop) must be sewn into the bottom of the waistband (“dropped” belt loops are cause for rejection) and the top of the belt loops shall be caught into the waistband curtain seam with a Rocap machine. The bottom of the center back loop shall be tacked to the trouser and the top of the loop tacked to the outside of the waistband.

SEAT

Seat outlet to measure a minimum of 2-3/4” to allow for alterations. Seat must be sewn with a Tandem Needle Machine.

STITCHING PRESSING & FINISHING:

Trouser must be stitched with matching thread and all stitching to show must be 10-11 stitches per inch. Trouser must be neatly pressed on Hothead Presses and properly shaped. Outseams and inseams must be pressed open. Trouser must be oven baked after pressing. Trouser must be cleaned and finished to eliminate loose threads.

LABELS:

Trouser must have a care label permanently affixed that also indicates the size. A paper ticket showing the size, fabric content, cut number, and WPL number must be on the outside of the waistband. Garment must be made in the United States of American and bear a union label.

CLASS “B” CARGO PANT – MALE

<u>DESIGN</u>	Cargo-style pant with five flat pockets (no pleats).
<u>FABRIC</u>	
Weight:	7 to 8 oz. per square yard. 65/35 Poly/Cotton with 11% stretch or 2 x 1 Twill with 6% stretch and soft-sanded finish. Milliken style 3969, finish 1952, Avondale Mills style 2026, or equivalent.
Thread:	3-ply Poly/Cotton Dual Duty Size 40 or larger.
Stitching:	All seams must be sewn with a least 8 to 10 stitches per inch.
Shrinkage:	Fabric must not shrink more than a maximum of 3.0 x 3.0 in W and F.
<u>COLOR</u>	CDC approved Olive Green (United – Avondale, Pro-Tuff – Milliken #02552, or equivalent.)
<u>POCKETS</u>	All pockets and pocketing are to be of body fabric.
Back	Two rear hip patch pockets finished to 6.5 x 6.5 with a 3/4 inch double fold hem. Pocket to have two pieces of loop 1 inch x 1 inch long placed along the top edge of hem and 1/2 inch in from the raw edge, properly aligned with the hook on the flap. The flap measures 7 inches in width by 2 1/4 inches finished. The pocket flap shall be closed with two pieces of hook 1 inch x 1 inch wide and should be invisible when pocket flap is closed. The flap shall be applied approximately 1 inch above the pocket and sewn first to the pant body in the open position, then folded down and topstitched 1/2 inch below the fold down, leaving no raw edges exposed under the flap. The pocket will have bar tacks at each side and the pocket flap at the edge vertically above the topstitch line. (See Bar Tacks below)
Front	Two slash-style (quarter top style) front bag pockets. Cut from trouser material with a minimum opening of 6.5 inches. A bar tack will be placed across the side seam at the top (parallel to the waist) and bottom (perpendicular to the side seam crossing each side) or the bag pocket opening. Topstitch the pocket opening.
Side	Two thigh pockets measuring 8.25 x 10.25, finished at 7.25 x 9.25 with covered diagonal zippers (7 inches – 8 inches) closed in the downward direction and toward the inseam on each leg positioned 4 inches below the bottom of the opening of the bag pocket. Zipper seam is to be 1 inch below the rear pocket corner edge.
Calf	One 5.75 x 12 pocket finished to 4.75 x 11 with a 5” covered zipper placed vertically in the center beginning 2 inches down from the top of the unfinished pocket. Closure to be at the top of the zipper. Pocket

placement is to be on the right out seam 5" below the bottom of the thigh pocket. Or, one 8.25 square pocket finished to 7.25 square with a 7 inch

covered zipper placed diagonally and closing in the downward direction beginning 1 inch below the top of the pocket.

Pocket Rust resistant brass with steel sliders, brass finished decorative pull (solid
Zippers: oblong or rectangle), size four teeth, 100% poly tape.

ZIPPER/FLY

45 nylon coil, black, 100% poly tape with locking slider zipper with pull, or #45 YKK or Talon memory lock brass zipper with brass bottom stop at the base of the zipper chain. A straight bar tack (parallel to the side seam) will be sewn at the bottom of the zipper stop through from the outside of the garment to the inside at the bottom of the fly. It shall be sewn through the zipper tape; the right and left fly and the right fly lining. The French fly closure, on the inside of the right fly, made of the shell material is recommended but optional.

DARTS

There are to be two darts in the back of trouser, one on each side, placed approximately 4 inches from the side seam.

WAISTBAND

To be 2 3/8 inches wide, finished, and lined with the specified waistband materials. The lining shall not be visible from the finished side of the garment. The waistband should be stitched through the finished side all the way through the lining the entire length of the waistband, leaving no raw edges inside the trouser. A 2.5 inches wide black poly curtain with 1/2 inch Snugtex, Flextrack, or equivalent (freedom fit optional) and 3/4 inch no roll stiffener. The top closure of the waistband shall be with two steel hook and eye closures with 7/8 inch stay or tape backing reinforcement behind each component. The hook and eye closures are placed one above the other to create a neat and even appearance. (Equivalent is 3 1/8 inch wide and shall close with two crush-proof hook and eye closures with 7/8" stay reinforcement behind each component. The waistband curtain must be attached with a rocap machine and must be made with QST industries black starspun III with style 1617 elastic banrol and stretch banrol II canvas. The trousers are to be made with a continuous closed waistband. The waistband shall be set on and shall be stitched below the lower edge through the outer fabric and waistband curtain.)

BELT LOOPS

Are to be 3/8 to 3/4 inch wide (3/4 inch is recommended) of two plies folded, finished on the underside, and top stitched 3/16 inch from each edge. There will be seven belt loops, one centered at the back seam, two to be placed just forward of the side seams, and the other four loops to be evenly spaced between these loops. The loops are to be tall enough to accommodate a 2 inch duty belt and sewn into the waistband at both top and bottom.

TROUSER CREASE

Front and back creases are to be permanently set with steam press and Creaset™ system, or equivalent, prior to the double knees being applied.

KNEES

Double knees of the same fabric as the pant will be placed on each knee area measuring the width of the pant leg and 10 inches in height. The top seam is approximately 9 1/2 inches below the crotch seam.

BAR TACKS

All stress points must be reinforced by bar tacks. These points include: zippers, the sides of all pocket openings, and pocket flaps. Additional bar tacks are acceptable, such as a (Δ) triangular bar tacks.

FINISHING

There are to be no raw edges on the interior of the garment and all threads should be trimmed. Trousers must be pressed completely and properly with side seams and inseam pressed open or the overlap seam being sewn and pressed all to the same side.

PACKAGING

Each garment is to be folded and placed in a plastic bag with the size and style label clearly visible.

LABELS

Must include the following information:

Style # (Optional)

Size: Indicate size: 28 - 64 in Short / Regular / Long Rise

Fabric Content / Washing Instructions

Date of Manufacture - "Made in USA of USA Components"

The female Class "B" cargo pant specifications encompass the same guidelines as described above. Reasonable accommodation will be given to female staff for cargo pant alternation for maternity needs.

CLASS "B" LONG SLEEVE SHIRT – FEMALE

FABRIC

Content: All synthetic tropical weave, 65% Dacron Polyester/35% Avril Rayon conforming to the following specifications:

Weight: 6.6 oz./yd. 2

Construction: 49 warp X 36 filling yarns per square inch. All yarns size 10/1 singles.

Air Permeability: Ft. 3/Min./Ft. 2 131 ASTM D 737-46

Tensile:	Break Strength 105 warp - 90 filling (lbs.)
Properties:	Tear Strength 9.7 warp - 8.5 filling (lbs.)
Pilling:	Minimum 4.9 rating

COLOR

Silvertan matching standard sample on display.

STYLE

Plain front coat style, form fitting, banded collar, and long sleeves with barrel cuffs. Two plain breast pockets with scalloped flaps. Shoulder straps. Full badge reinforcement. Matching inside yoke and collar band of high luster Dacron/Cotton Poplin.

COLLAR & STAND

Style and dimension, as sample on display. Collar points to measure 2 7/8" with mylar stays. Collar height at rear 1-1/2". Top stitched 1/4" off edge. Collar stand to be 1-5/16" at rear and to be interlined with stabilized Mellopress, with "Crease N Tack" in band.

FRONT

The front shall have a top center 1-1/2" wide with two rows of stitches 7/8" apart. Stitching on the top center is not to be visible on the turn-back facing. The right front shall have six buttonholes spaced 3-1/2" apart and to be set 3/4" from edge. Second button to be spaced 2 1/2" from top button, balance of buttons spaced 3 1/2" apart.

SHOULDER STRAPS

Style and dimensions as sample. Asymmetrical shape top stitched 1/4" off the edge to be set on yoke with leading top stitch conforming with front joining seam. To measure 2" at sleeve tapering to 1 3/8" and set not more than 1/2" from folded collar. Cross stitched approximately 2" from sleeve seam.

BADGE REINFORCEMENT

Two-ply sling 1" wide centered over left pocket and stitched to shoulder seam and flap setting stitch. To have two buttonhole eyelets approximately 3/4" from top of pocket flap spaced 3/4" apart and centered on sling.

POCKETS

Two plain breast pockets. Pocket to measure 5" wide, 5" deep. Each pocket is to have Velcro tape 3/4" long by 1/2" wide, positioned on both edges of pocket to correspond with outer scalloped flap points, as sample.

FLAPS

Deep scalloped design to measure 5-1/4" across, 2-1/4" in depth at center point, and 1-3/4" at sides. Secured to shirt front approximately 1/4" above pocket. Left flap to have invisible pencil opening 1-1/4". Both flaps to be interlined with stabilized Mellopress #550. Underside of flap to have Velcro tape 3/4" long by 1/2", wide positioned on outer points of both pocket flaps, as sample.

SLEEVES

Long sleeves to be cut straight and whole with 4-3/4" sleeve vent. Sleeve shall have a one piece round elbow reinforcement and vent facing. Elbow reinforcement shall extend into the sleeve closing seam. Lower facing shall measure approximately 1/2" in width.

CUFFS

To measure 2 1/2" in depth with rounded corners as sample. With two button adjustable cuff. Both cuffs to be interlined with stabilized #550 Mellopress.

MILITARY CREASES

Seven baked in sharp military creases on all shirts. One crease on each front to be centered vertically through pocket and flap. Spacing for military creases on shirt back to be proportionate to the size of the shirt. Military creases on both sleeves to be centered on the middle of the shoulder strap.

BUTTONS

First grade 22 Ligne melamine to match.

STITCHING

Single needle throughout. All top stitched 1/4" off the edge. Sleeve inserting and side close felling, safety stitched.

THREAD

All sewing threads to be fast color polyester core polyester wrap to match.

CONSTRUCTION

Collars, flaps, and shoulder straps are made by the conventional construction. Top ply, bottom ply, and interlining are first stitched together, then turned rightside out and finally topstitched.

COUNTRY OF MANUFACTURE

All raw materials and assembly thereof made in the U.S.A.

CLASS "B" SHORT SLEEVE SHIRT – FEMALE

FABRIC

Content: All synthetic tropical weave 65% Dacron Polyester/35% Avril Rayon conforming to the following specifications:

Weight: 6.6 oz./yd. 2
Construction: 49 warp X 36 filling yarns/square inch. All yarns size 10/1 singles or equivalent.
Air Permeability: Ft. 3/Min/Ft. 2 131 ASTM D 737-46
Tensile: Break Strength 105 warp - 90 filling (lbs.)
Properties: Tear Strength 9.7 warp - 8.5 filling (lbs.)
Pilling: Minimum 4.9 rating

COLOR

California Department of Corrections Silvertan.

STYLE

Plain front coat style, form fitting, collar attached, short sleeves. Two plain breast pockets with scalloped flaps. Shoulder straps. Full badge reinforcement. Matching inside yoke and collar band of high luster Dacron/Cotton Poplin.

COLLAR

Convertible collar shall be one piece and measure 2-7/8" long at points. The collar shall be made with permanent stays and stabilized with #285 Mello Press. Collar to be topstitched 1/4" off the edge.

FRONT

The front shall have a top center 1-1/2" wide with two rows of stitches 7/8" apart. Stitching on the top center is not to be visible on the turn-back facing. The right front shall have six button holes spaced 3-1/2" apart and to be set 3/4" from the edge. Second button to be spaced 2-1/2" from top button, balance of buttons spaced 3-1/2" apart.

SHOULDER STRAPS

Asymmetrical shape topstitched 1/4" off the edge to be set on yoke with leading topstitch conforming with front joining seam. To measure 2" at sleeve tapering to 1-3/8" and set not more than 1/2" from folded collar. Cross stitched approximately 2" from sleeve seam.

BADGE REINFORCEMENT

Two-ply sling 1" wide centered over the left pocket and stitched to shoulder seam and flap setting stitch. To have two buttonhole eyelets approximately 3/4" from top of pocket flap, spaced 3/4" apart, and centered on the sling.

POCKETS

Two plain breast pockets with rounded corners. Pocket to measure 5" wide, 5" deep. Each pocket to have Velcro tape 3/4" long by 1/2" wide, positioned on both edges of pocket to correspond with outer scalloped flap points.

FLAPS

Deep scalloped design to measure 5-1/4" across, 2-1/4" in depth at center point, and 1-3/4" at sides. Secured to shirt front approximately 1/4" above pocket. Left flap to have invisible pencil opening 1-1/4". Both flaps to be interlined with stabilized Mello Press #550. Underside of flap to have Velcro tape 3/4" long by 1/2" wide, positioned on outer points of both pocket flaps.

SLEEVES

Sleeves are to be straight and whole, to have 3/4" hem, and to finish approximately 8-1/2" long from shoulder seam.

MILITARY CREASES

Seven baked in sharp military creases on all shirts. One crease on each front to be centered vertically through pockets and flaps. Spacing for military creases on shirt back to be proportionate to the size of the shirt. Military creases on both sleeves to be centered on the middle of the shoulder strap.

BUTTONS

First grade 22 Ligne melamine to match.

STITCHING

Single needle throughout. All topstitched 1/4" off the edge. Sleeve inserting and side close felling, safety stitched.

THREAD

All sewing threads to be fast color polyester core, polyester wrap to match.

CONSTRUCTION

Collars, flaps, and shoulder straps are made by the conventional construction. Top ply, bottom ply, and interlining are first stitched together, then turned rightside out, and finally topstitched.

COUNTRY OF MANUFACTURE

All raw materials and assembly thereof made in the U.S.A.

CLASS "B" TROUSER – FEMALE

FABRIC

65% Dacron Polyester/35% Rayon. Oz/Linear Yard (60" width). Post Cured Fabric Weight: 13-13 1/2. Tensile Strength: 145 Lbs. Warp/65 Lbs. fill. Tear Strength: 2,000 Grams Warp & Fill. Gabardine weave. Forest Green.

DESIGN

Trouser shall be manufactured from a women's uniform trouser pattern with a plain front, and one dart on each rear panel above the hip pockets. The slack shall be straight leg design. The slack shall incorporate two quarter top front pockets and two hip pockets.

POCKETS

The two front pockets will be quarter top style with an opening of 5-1/2" and a depth of 5-1/4", measured from the bottom of the opening. Front pockets shall have straight bartacks (use of triangle bartacks will be cause for rejection) at the top and bottom of pocket openings. Pockets shall be constructed using the stitch, turn, and topstitch method. Pocket facings shall be made of the basic fabric and shall measure a minimum of 2" in width.

The two hip pockets shall have a 5" wide opening and a 6" depth, measured from the bottom of the pocket opening. Hip pockets shall be constructed using the double welt method on a REECE PW Machine and the welts shall be finished in such a manner that there is no topstitching (topstitched hip pocket welts shall be cause for rejection). The corners of the hip pocket openings shall have firm straight bartacks for reinforcing strength (triangle bartacks are unacceptable). The left hip pocket shall have a centered tab made of basic cloth inserted into the top welt with bartacks at the top and bottom of

the tab to form an opening for a button. A button shall be located below the bottom welt corresponding in location with the tab.

The watch pocket shall be located on the right front at the waistband. This pocket shall have a minimum opening and depth of 2-3/4". The front of the pocket shall be made of pocketing fabric. The back of the pocket shall be made of basic fabric, and the two pieces are securely stitched together. Each corner of the pocket opening shall have firm straight bartacks.

POCKETING

The pocketing shall be 70% polyester/30% cotton, 2.9 oz. per square yard (60" width) with a minimum 78 x 64 count. Pocketing must have a durable press finish and the color of the pocketing must be black.

WAISTBAND

The trouser will be made with a stretch waistband system, which is designed to provide the wearer with a more comfortable and better fitting trouser. The waistband shall be constructed using a "closed method" and shall measure 2" wide when finished. The waistband closure shall be accomplished with a crush proof hook and eye. The hook and eye shall be reinforced with stays made of a non-woven fabric that are anchored by the topstitching for the fly facing and curtain. This topstitching must be to the top of the waistband. The waistband must be topstitched 1/16" below the waistband seam for added strength. The top portion of the inside of the waistband is to consist of the same fabric as used for pocketing (70% polyester, 30% cotton - minimum 80 X 62 (+/-) 2 count). The fabric is to be cut on the bias for maximum comfort. To be 1-3/4" wide and to finish 1-1/8" wide after construction.

Upper waistband curtain to be inner lined with stretch Ban-Rol canvas. This canvas fabric consists of a warp of 47 ends of texturized nylon and a fill of 34 ends of 750 denier polyester monofilament. The woven fabric is coated with latex, which completely encapsulates all years. This finish canvas fabric weighs 12.0 oz/yd². The canvas will be cut 1-3/8" monofilaments running vertically and have a 10% stretch.

The bottom portion of the waistband curtain will be a blend of 32% nylon, 38% polyester, 18% rubber (3 strands) 11% lycra and 1% acrylic woven 1-7/8" wide and to finish a minimum 1-5/8" wide. To have a minimum of 40% stretch characteristics.

NOTE: In a performance stretch waistband, the upper and lower portion of the band will perform different functions.

The upper portion should allow a comfort fit at the waist when bending or sitting and must maintain a crisp, clean appearance at the outer waistband. This part of the band will stretch 10% and be firm enough to prevent waistband rollover.

The bottom portion of the waistband stretches over the hip to give support to the lower back and abdomen. In addition, this high stretch portion of the band should constantly be pressed up by the hips, preventing the slack from slipping down while being worn, even if heavy keys, change, or other items are carried in the pockets or on the belt. The three rubberized strands ensure that shirts stay tucked in for neat appearance.

FLY

Trouser shall have a metal memory lock zipper. There shall be a French Fly tab closure on the inside of the right fly. The tab shall be double ply made of the basic cloth (tabs made of pocketing material or a “grown on” French Fly will be cause for rejection). The right fly shall be lined with the same fabric as the waistband curtain and pocketing. The fly lining shall be sewn to the left fly below the zipper in a neat and durable manner. A button shall be located on the left fly corresponding with the French Fly tab to provide a clean and comfortable closure. There shall be a firm straight bartack at the bottom of the fly going through the zipper.

BELT LOOPS

There shall be a minimum of seven belt loops 3/4” in width of double thickness. Each loop must have a non-woven interlining. All loops (except for the back center loop) must be sewn into the bottom of the waistband (“dropped” belt loops are cause for rejection) and the top of the belt loops shall be caught into the waistband curtain seam with a Rocap machine. The bottom of the center back loop shall be tacked to the trouser and the top of the loop tacked to the outside of the waistband.

SEAT

Seat outlet to measure a minimum of 2-3/4” to allow for alterations. Seat must be sewn with a Tandem Needle Machine.

STITCHING PRESSING & FINISHING:

Trouser must be stitched with matching thread and all stitching to show must be 10-11 stitches per inch. Trouser must be neatly pressed on Hothead Presses and properly shaped. Outseams and inseams must be pressed open. Trouser must be oven baked after pressing. Trouser must be cleaned and finished to eliminate loose threads.

LABELS:

Trouser must have a care label permanently affixed that also indicates the size. A paper ticket showing the size, fabric content, cut number, and WPL number must be on the outside of the waistband. Garment must be made in the United States of American and bear a union label.

CLASS “B” CARGO PANT - FEMALE

<u>DESIGN</u>	Cargo-style pant with five flat pockets (no pleats).
<u>FABRIC</u>	
Weight:	7 to 8 oz. per square yard. 65/35 Poly/Cotton with 11% stretch or 2 x 1 Twill with 6% stretch and soft-sanded finish. Milliken style 3969, finish 1952, Avondale Mills style 2026, or equivalent.
Thread:	3-ply Poly/Cotton Dual Duty Size 40 or larger.
Stitching:	All seams must be sewn with a least 8 to 10 stitches per inch.
Shrinkage	Fabric must not shrink more than a maximum of 3.0 x 3.0 in W and F.
<u>COLOR</u>	CDC approved Olive Green (United – Avondale, Pro-Tuff – Milliken #02552, or equivalent.)
<u>POCKETS</u>	All pockets and pocketing are to be of body fabric.
Back	Two rear hip patch pockets finished to 6.5 x 6.5 with a 3/4 inch double fold hem. Pocket to have two pieces of loop 1 inch x 1 inch long placed along the top edge of hem and 1/2 inch in from the raw edge, properly aligned with the hook on the flap. The flap measures 7 inches in width by 2 1/4 inches finished. The pocket flap shall be closed with two pieces of hook 1 inch x 1 inch wide and should be invisible when pocket flap is closed. The flap shall be applied approximately 1 inch above the pocket and sewn first to the pant body in the open position, then folded down and topstitched 1/2 inch below the fold down, leaving no raw edges exposed under the flap. The pocket will have bar tacks at each side and the pocket flap at the edge vertically above the topstitch line. (See Bar Tacks below)
Front	Two slash-style (quarter top style) front bag pockets. Cut from trouser material with a minimum opening of 6.5 inches. A bar tack will be placed across the side seam at the top (parallel to the waist) and bottom (perpendicular to the side seam crossing each side) or the bag pocket opening. Topstitch the pocket opening.
Side	Two thigh pockets measuring 8.25 x 10.25, finished at 7.25 x 9.25 with covered diagonal zippers (7 inches – 8 inches) closed in the downward direction and toward the inseam on each leg positioned 4 inches below the bottom of the opening of the bag pocket. Zipper seam is to be 1 inch below the rear pocket corner edge.
Calf	One 5.75 x 12 pocket finished to 4.75 x 11 with a 5” covered zipper placed vertically in the center beginning 2 inches down from the top of the unfinished pocket. Closure to be at the top of the zipper. Pocket placement is to be on the right out seam 5” below the bottom of the thigh

pocket. Or, one 8.25 square pocket finished to 7.25 square with a 7 inch covered zipper placed diagonally and closing in the downward direction beginning 1 inch below the top of the pocket.

Pocket Rust resistant brass with steel sliders, brass finished decorative pull (solid
Zippers: oblong or rectangle), size four teeth, 100% poly tape.

ZIPPER/FLY

45 nylon coil, black, 100% poly tape with locking slider zipper with pull, or #45 YKK or Talon memory lock brass zipper with brass bottom stop at the base of the zipper chain. A straight bar tack (parallel to the side seam) will be sewn at the bottom of the zipper stop through from the outside of the garment to the inside at the bottom of the fly. It shall be sewn through the zipper tape; the right and left fly and the right fly lining. The French fly closure, on the inside of the right fly, made of the shell material is recommended but optional.

DARTS

There are to be two darts in the back of trouser, one on each side, placed approximately 4 inches from the side seam.

WAISTBAND

To be 2 3/8 inches wide, finished, and lined with the specified waistband materials. The lining shall not be visible from the finished side of the garment. The waistband should be stitched through the finished side all the way through the lining the entire length of the waistband, leaving no raw edges inside the trouser. A 2.5 inches wide black poly curtain with 1/2 inch Snugtex, Flextrack, or equivalent (freedom fit optional) and 3/4 inch no roll stiffener. The top closure of the waistband shall be with two steel hook and eye closures with 7/8 inch stay or tape backing reinforcement behind each component. The hook and eye closures are placed one above the other to create a neat and even appearance. (Equivalent is 3 1/8 inch wide and shall close with two crush-proof hook and eye closures with 7/8" stay reinforcement behind each component. The waistband curtain must be attached with a rocap machine and must be made with QST industries black starspun III with style 1617 elastic banrol and stretch banrol II canvas. The trousers are to be made with a continuous closed waistband. The waistband shall be set on and shall be stitched below the lower edge through the outer fabric and waistband curtain.)

BELT LOOPS

Are to be 3/8 to 3/4 inch wide (3/4 inch is recommended) of two plies folded, finished on the underside, and top stitched 3/16 inch from each edge. There will be seven belt loops, one centered at the back seam, two to be placed just forward of the side seams, and the other four loops to be evenly spaced between these loops. The loops are to be tall enough to accommodate a 2 inch duty belt and sewn into the waistband at both top and bottom.

TROUSER CREASE

Front and back creases are to be permanently set with steam press and Creaset™ system, or equivalent, prior to the double knees being applied.

KNEES

Double knees of the same fabric as the pant will be placed on each knee area measuring the width of the pant leg and 10 inches in height. The top seam is approximately 9 1/2 inches below the crotch seam.

BAR TACKS

All stress points must be reinforced by bar tacks. These points include: zippers, the sides of all pocket openings, and pocket flaps. Additional bar tacks are acceptable, such as a (Δ) triangular bar tacks.

FINISHING

There are to be no raw edges on the interior of the garment and all threads should be trimmed. Trousers must be pressed completely and properly with side seams and inseam pressed open or the overlap seam being sewn and pressed all to the same side.

PACKAGING

Each garment is to be folded and placed in a plastic bag with the size and style label clearly visible.

LABELS

Must include the following information:

Style # (Optional)

Size: Indicate size: 28 - 64 in Short / Regular / Long Rise

Fabric Content / Washing Instructions

Date of Manufacture - "Made in USA of USA Components"

The female Class "B" cargo pant specifications encompass the same guidelines as described above. Reasonable accommodation will be given to female staff for cargo pant alternation for maternity needs.

CLASS "B" NON-WATERPROOF JACKET

FABRIC

Shell: Cloth - 330 Denier Cordura Nylon (warp), 3 ply Taslanized Nylon (filling). Weave - Plain treated with Fluorcarbon Water and Stain Release Agents. Weight (uncoated) - 5.5 oz. per sq. yard. Color - Forest Green.

Permanent Lining: 104 x 86 thread count. 100% Nylon Taffeta. Color-Black.

Zip Out Lining: Face - 100% Nylon Taffeta. Batt - Quilted 200 Gram body with 150 Gram sleeves Thinsulate by 3M. Back - 100% Nylon Taffeta.

Collar: 1/2" black Orlon pile.

DESIGN

The jacket shall be a full cut, waist length model with zip in - zip out liner, zipper front and shirred waistband. Coat construction shall be used throughout with body and sleeves being fully lined.

BODY DETAIL

The front shall be plain with patch pockets, flaps and badge tab. For shape retention, the front shall be interlined with heavy weight Pellon. The inside facings shall be made of outer fabric and are to be sewn on top of the nylon lining, which extends to the front edge of the jacket. There shall be a one piece back. There is to be a separate 2-1/2" waistband shirred with 2" heavy duty elastic. The entire waistband is to be shirred with the exception of an area 5-1/2" on either side of the front opening, and side zipper entry on either side, approximately 9" in length and secured by a nylon zipper and snap closure. The shoulders shall have pads. A self goods reinforcement strip shall be sewn on the inside of the jacket joined at the top of the waistband and extending from side to side.

INSIDE DETAIL

On the left side of the coat, there shall be a gun pocket installed on the permanent lining of the coat to accept a small frame hand gun. The gun pocket shall have a minimum opening of 4-1/2" and be a minimum of 6" deep. The gun pocket shall be furnished with a strap and snap closing. Bartacks shall reinforce the opening. There shall be two cut-in pockets on the left and right sides measuring approximately 5-1/2" wide and 6" deep.

ZIP-OUT LINER

Shall be full body and sleeves with inside right pocket and shall be constructed to allow entry to gun pocket and through the side zip openings. The liner sleeves shall have knit wristlets. The liner will be attached to the sleeves by either method: with a male and a female snap or with a button and buttonhole or a loop.

SLEEVES

The sleeves shall be coat style set in with a single needle machine. The bottom of the sleeve shall have a gusset opening and close with a storm cuff with velcro closure for adjustable fit. The cuff shall be interlined with Pellon. There shall be an elastic sleeve loop for liner stability on the inside of the cuff.

POCKETS

There shall be two patch pockets with box pleats, finishing approximately (minimum dimensions) 6-1/4" wide and 7-1/2" deep. Flaps shall be scalloped and self lined. They shall close with velcro on the points and with a centered buttonhole. The pockets shall be interlined with Poly/Cotton twill in such a way as to create hand-warmer pockets with an opening of approximately 5-1/2" on the side. The left patch pocket is to have a pencil opening at the top of the flap. Both the pockets and the flaps are to be bartacked.

COLLAR

The collar shall be made using self material. It shall be interlined with Pellon. There shall be a detachable fur collar using Orlon pile. This collar is to be attached to the permanent collar with buttons and buttonholes.

EPAULETS

The epaulets shall be made of self goods. They shall be sewn into the sleeve head seam, X-stitched, and tacked to the jacket at the neck.

BADGE TAB

The badge tab shall be made of outer fabric 1" wide with 2 metal eyelets spaced vertically apart. It shall be centered 2-1/2" above the left pocket flap.

ZIPPER

There shall be a YKK #5 molded nylon zipper in the front and with a minimum of 9" nylon zippers on each side vent.

BUTTONS AND SNAPS

The pocket flaps and epaulets shall be secured with 24 ligne Gold Eureka metal buttons. Flaps and epaulets shall close with 24 ligne Gold Eureka metal buttons. Side zippers shall be secured by bottom snaps.

THREAD

All sewing is to be done with Polyester core thread or 100% Spun Polyester thread.

SIZE TAG AND CARE INSTRUCTIONS

Each jacket shall have a sewn in label giving care instructions and shall be marked with lot number, size, fiber content and WPL number.

FINISHING AND PRESSING

All loose threads shall be removed. Each jacket shall be pressed and shaped properly.

WARRANTY

One year against workmanship or fabric defects.

CLASS "B" NON-WATERPROOF 3/4 LENGTH FOUL WEATHER JACKET

FABRIC

330 Denier Cordura Nylon (warp), 3 Ply Taslanized Nylon (filling). Weave: Plain treated with durable fluorocarbon water and stain release agents. Weight (uncoated: 5.5 oz. per sq. yard (± 4 oz.)). Break Strength (lbs): 190 warp (min.) 110 fill (min.). Tear Strength: 38 (min.). Count: 64 warp, 38 fill. Shrinkage: warp and fill 2% max. Color Fastness & Crocking: Good. Coating: Non-ravel 1/4 oz. Urethane. Color: Green.

PERMANENT LINING

Cloth type: 100% Nylon Taffeta. Weave: Plain. Denier: 70 warp, 70 fill. Fibers: Nylon #66 continuous filling yarns with 34 filaments. Melting Point: 450 F. Weight 1.8 oz. per sq. yard. Warp: 104 (± 2). Fill: 86 (± 2). Tear Strength (lbs.): Min. 3.5 warp & min. 2.1 fill. Breaking Strength: Min. 125 warp - min., 85 fill. Maximum Shrinkage: Less than 2% warp and fill. Color Fastness & Crocking: Good. Color: Black.

INTERLINING

One hundred percent Cotton Osnaburg. Weight: 3.45 yards per pound. Count: 30 warp, 24 fill. Break Strength: 60 lbs. warp, 35 lbs. fill. Maximum Shrinkage: 3-4% warp and fill. The following parts must be interlined: collar, collar stand, epaulets, pocket flaps and fronts.

GENERAL STYLING

Hip length cut from a modern uniform jacket pattern. Two-way zipper front opening and left and right side zippered vents for easy access to equipment. To have detachable pile collar, wind collar, permanent collar, collar stand, two-piece set-in sleeves, bi-swing back; shoulder epaulets, upper hanging and lower slash pockets. To have zip-out Thinsulate Liner and permanent Thinsulate Lining in sleeves.

Garment parts to be cut employing Garber GGT 591 traveling, conveyORIZED and computerized cutting system.

REMOVABLE LINER

There shall be a zip-out sleeveless insulated liner that incorporates CS-200 Thinsulate Thermal Insulation in the body. The insulation shall be quilted to 86 pick nylon on the face side of the liner and nylon tricot on the backing.

The perimeter of the liner shall be bound with black nylon tape and the liner shall have a zipper track to allow the liner to zip out of the jacket. Liner to be removable by means of a 54" aluminum zipper. The left front of the liner shall have a patch pocket measuring approximately 6" x 6".

SLEEVES

Two piece, coat style, set in, with shoulder pads and genuine leather trim. The sleeves shall be permanently lined incorporating CS-100 Thinsulate. The insulation shall be quilted to 86 pick nylon.

EPAULETS

The epaulets shall be 2-1/4" wide at their widest point. The points of the epaulets shall finish at the collar joining seam of the coat, fastened with a buttonhole and 24 ligne uniform button. The epaulets shall be functional and removable. They shall be placed under and folded over two loops constructed of self material placed approximately 2-3/4" apart sewn to either side of shoulder seams. The loop closest to the sleeve seam shall measure 2" x 3/8". The loop closest to the collar shall measure 1-3/4" x 3/8". Unfolded, the epaulet shall measure approximately 13" in length.

COLLAR AND STAND

The permanent collar and collar stand shall be made of two plies of the basic fabric plus the interlining. The interlining shall be sewn to the under collar and under collar stand using an eight point star stitch. The collar points shall be well shaped and symmetrical. The detachable collar will consist of a layer of pile fabric and one layer of polyester/cotton pocketing. The under collar portion of the detachable collar shall consist of two plies of the basic fabric. There will be three buttonholes on both sides of the detachable collar for attachment to the jacket. Collar Pile: 100% Acrylic Face, 100% Polypropylene back. Weight: 27-28 oz. per linear yard. Pile Height: 3/8". Finish: High Lustre Seal Finish. Knit Collar: Rib knit 1 x 1, 100% Polyester. Minimum width: 1".

WRISTLETS

Shall be black 100% Polyester, 1 x 1 rib knit.

BUTTONHOLES

Cut first with #8 gimp. Thread ends to be bartacked.

POCKETS

The upper pockets shall be inside hanging pockets with scalloped flap with 24 ligne button and buttonhole. Flaps to be self-lined with snap closure system. The male portion of the snaps shall be located on the lower corners on the underside of the flaps. The female portion of the snaps shall be in a corresponding position on the front of the jacket to provide a neat and secure closure. The lower pockets shall be a slash pocket with 7/8" welt. The welt shall be trimmed with genuine leather. The inside nylon taffeta lining shall have a single inside pocket double piped. This shall be approximately 5-1/2" wide x 8" deep and shall be on the left front.

BI-SWING BACK

The bi-swing shall be approximately 12" in length and 1-1/2" in depth. It shall be constructed with an elasticized anchor so that the bi-swing will be snapped back into proper position after being extended. The elastic shall be a 1" elastic braid.

BARTACKS

Bartacks shall be used on the zipper of the quilted liner, at both male and female ends, and on both female ends of the storm liner (6 bartacks in all). The pocket on the quilted liner shall also be bartacked at each upper corner. Bartacks shall also be used to join binding ends on the armholes of the quilted liner and storm liner, and at any other binding ends. Badge tab shall be bartacked at each end.

SLIDE FASTENERS

The front zipper shall use a Delrin, 2-way, size #10, 24" long, color black. The zip out lining zippers shall be aluminum, size #3, non-locking. Side zippers to be nylon, 2-way, size #3, 12" long, color black.

EYELETS

Eyelets for the badge tab shall be spaced 1-1/8" center to center and shall be size 00 invincible brass.

BADGE TAB

To be made of self material with two metal eyelets. The bottom of the badge tab shall be approximately 5/8" above the left pocket flap.

LIMITED WARRANTY

The contract garments shall carry manufacturers' printed warranty hang tag. A sample warranty hangtag must accompany the bid package as well. The tag shall instruct the owner of their rights under the warranty.

The limited warranty shall contain at minimum the following:

Warranty Coverage: Manufacturer agrees to warrant to the original purchaser that the product will be free from defects in materials and workmanship for a period of three years from date of purchase.

Warranty Service: Should a covered product become defective during the warranty period, simply return it to the manufacturer with dated proof of purchase. The manufacturer agrees to repair or replace at its option any item determined to be defective and will return to purchaser at no charge.

Limitations: This warranty does not cover abnormal wear and tear, nor the color fastness of fluorescent fabrics, nor damage from chemicals, fire misuse, accident or negligence. This warranty only applies to the original purchaser of the covered product and is not transferable.

CLASS "B" WATERPROOF FOUL WEATHER JACKET

INSULATION

3M Thinsulate, with a scrim covering front and back to prevent migration of insulation fibers. Lining must be quilted horizontally with a minimum of a 6" railroad pattern for maximum thermo retention. Excess stitching and openings in liner cause extreme loss of body heat.

BODY

3M Thinsulate CDS 200 composed of 65% Polyolefin microfibers and 35% 6 Denier Polyester staple fibers (by weight). Shall weigh approximately 200 grams/square meter horizontally quilted.

SLEEVES

3M Thinsulate CDS 100 composed of 65% Polyolefin microfibers and 35% 6 Denier Polyester staple fibers (by weight). Shall weigh approximately 100 grams/square meter horizontally quilted. The perimeter of the liner shall be bound with black nylon tricot tape and the liner shall have a zipper track to allow the liner to zip out of the jacket.

The liner sleeves shall have knit wristlets of 1 x 1 ribbed 100 percent nylon and the liner sleeves will have a female snap by the insleeve seam no more than 1" from the end of the sleeve. Attached to the jacket sleeve in a corresponding location will be a tab made of shell material with a male snap. The tab and snap are used to secure the liner sleeves - use of a button and buttonhole or loop is unacceptable. The liner shall have a left breast patch pocket. Each sleeve hem must be finished with bias tape so there are no raw edges.

The liner shall be designed with vents corresponding with the zippered side vents on the jacket to allow easy access to weapon or equipment.

BACK

There shall be a one piece back with a curved bi-swing for ease of movement. The bi-swing shall be approximately 12" in length and 1-1/2" in depth. It shall be constructed with an elasticized anchor so the bi-swing will snap back into proper position after being extended. It shall be constructed with an elasticized anchor made of a 2" wide strip of Lycra so the bi-swing will snap back into proper position after being extended.

INTERLINING

One hundred percent Cotton Osnaburg, 3.45 yards/lb. with maximum shrinkage of 3 to 4 percent in warp and fill. Interlining to be used in collar, pocket flaps, shoulder straps, front waistband, and storm front.

POCKETS

There shall be a box pleated (inverted pleats are cause for rejection) patch pocket on each front of the jacket. The box pleats shall be approximately 1-1/4" wide. The pockets shall be approximately 7-1/2" wide and 8" in depth. Pockets shall be constructed with hand warmer openings on the side. The surface portion of the hand warmer pockets will be the jacket front and the top part of the pocket (the area coming in contact with the back of the user's hand) will be black Kasha. The top and bottom of the side openings shall be securely bartacked.

The patch pockets will have an opening at the top underneath the scalloped flaps (any other style flap is unacceptable). The top of each patch pocket must be bound with black nylon binding. The top entry pockets shall be made of black Kasha.

The left front pocket will have a pencil compartment opening on the inside corner of the pocket flap. The opening will be reinforced by bartacks.

The scalloped pocket flaps shall have a metal snap closure system. The male portion of the snaps shall be located on the underside of each flap and the female portion of the snaps shall be in a corresponding location on the breast pockets to provide a neat and secure closure. Each flap shall have a dummy buttonhole with a 24 Ligne metal button on top of the flap attached with a kottter key on the bottom side of the flap.

The jacket design will include an inside left breast pocket. The pocket shall have a minimum width of 6" and a minimum depth of 8-1/4" (measured from the bottom of the pocket opening). The inside pocket will incorporate a zipper closure system utilizing a 6" CFC-256B2 zipper that is made with bottom stops at both ends.

ELASTIC WAISTBAND

Separate waistband shall be elasticized in the back. There shall be two rows of stitching each 1/2" apart, centered on the waistband, and extending through the elastic. The elastic shall be securely tacked at each end. There will be a zipper sewn into each side for access. Snap tabs shall be sewn into the waistband for closure of the side tab.

SLEEVES

Two piece, coat style sleeves set in. The sleeves shall be constructed with 7" zippers (black nylon) on the underseams. This system permits emblem attachment without puncturing the Gore-Tex by allowing access to the shell. Sleeve hems must be trimmed with black leather (approximately 1/8" to show). Leather must be attached with two rows of stitching. Shoulders must incorporate foam shoulder pads for shape.

COLLAR

The collar shall be produced using two plies of the shell fabric plus the interlining. The interlining shall be sewn to the undercollar using an eight point star stitch. The collar points shall be well shaped and symmetrical. The front storm flap shall extend to the top of the collar. Collar and collar interlining must be cut on bias.

EPAULETS

Jacket shall be designed with removable epaulets measuring approximately 2-1/2" at the widest point at the sleeve head and tapering to 2" at the narrow end. The point of the epaulet shall finish at the collar joining seam. It shall be fastened with a 24 ligne metal uniform button and buttonhole.

STORM FLAP

There shall be a double front storm flap; one on top and one under the top storm flap. The top storm flap will finish approximately 2-1/2" wide and will extend from the bottom of the waistband to the top of the collar point. There shall be six black gun metal snaps centered down the top storm flap. The under storm flap shall finish approximately 1-3/4" wide and will extend from the bottom of the waistband to the top of the collar point. The male portion of the snaps shall be positioned on the under storm flap to correspond to the placement of the snaps on the top storm flap to provide a neat and secure closure.

SIDE VENTS

The jacket shall be designed with side vents to allow for easy access to equipment. The vents shall incorporate 10" zippers. At the bottom of each vent there shall be a tab and snap closure system to prevent gaping between the front and rear portion of the jacket when the side zippers are in the full upward position.

BADGE TAB

To be made of self material with two metal eyelets. The bottom of the badge tab shall be 2-1/4" - 2-1/2" above the left pocket flap.

FRONT ZIPPER

The front zipper opening shall be accomplished with a two way pull; heavy duty #5 Vislon nylon molded zipper. Zipper will extend from bottom of waistband to collar seam.

KNIT WIND COLLAR

There shall be a knit wind collar of 1 x 1 ribbed spun nylon sewn into the collar seam, measuring 14" long by 1-1/2" wide at the center.

SEAM WATERPROOFING

Seams shall be taped with 7/8" two layer Gore seam tape. There shall be no stitching through the LTD liner except those seams that are waterproofed. There will be metal eyelets on the sleeve bottoms and above the front and back waistband, for water drainage in laundering.

OUTER SHELL

Performance Taslan. Warp: 70/34 Denier Nylon. Filling: 2 ply 70/34 Denier Nylon. Weight: 3.10 oz. per square yard. Break Strength: Warp-221 lbs. (min.). Filling-141 lbs. (min.). Tear Strength: Warp-7.5 lbs. (min.). Filling-6.3 lbs. (min.). Porosity: 6-7 CFM Abrasion (Raised Diaphragm): 86 strokes. Colorfastness and Crocking: Good. Color: Forest Green. To ensure maximum comfort and performance only two-ply Taslan will be accepted.

WATERPROOF BREATHABLE LINING

Must be Gore-Tex LTD liner from W.L. Gore (no substitutes). The waterproof breathable lining shall conform to the following requirements:

CHARACTERISTIC	REQUIREMENT	TEST METHOD
Moisture Vapor Transmission Rate (g/m ² /24hr) Procedure B Procedure BW	600 Minimum 5,000 Minimum	ASTM E 96-80 ASTM E 96-80
Hydrostatic Resistance (psi)	90 Minimum	FED-STD-191A 5512
Water Permeability		
Initial	No Leakage	FED-STD-191a 5516

After Cold Flex Warp Fill	No Leakage No Leakage	ASTM D 2097-69 (1980)
After 100 Hours of Continuous Wet Flex (Agitation)	No Leakage	AATCC 135 FED-STD-191A5516
After Dry Cleaning	No Leakage	FED-STD-191A 5516
After Synthetic Pers- piration	No Leakage	Gore QCTM 510 FED-STD-191A 5516
After Sustained Pressure	No Leakage	BS 3424: Part 26:1990 Method 29A
After Sustained Pressure After Exposure to Contamination	No Leakage	Gore MCTM 552 BS 3424: Part 26:1990 Method 29A

BASIC STYLING

Waist length, single breasted, Gore-Tex LTD breathable waterproof lining, removable Thinsulate body/sleeve liner, and front zipper storm front closure. Other features include a bi-swing back, sleeve zippers, scalloped pocket flaps, box pleated patch pockets with hand warmer openings, collar, knit wind collar, and zippered side vents.

REMOVABLE LINER

There shall be a zip-out insulated liner that incorporates CDS-200 Thinsulate Thermal Insulation in the body portion of the liner and CDS-100 Thinsulate Thermal Insulation in the sleeves. The insulation shall be quilted to black 86 pick nylon on the face side of the liner and nylon tricot on the backing.

SHELL FOR REMOVABLE LINER

86 pick. 100% Nylon Taffeta. Weave: Plain. Denier: Warp 70, Fill 70. Weight: 1.8 oz./square yard. Color: Black (any other shade is cause for rejection).

SIZE TAG AND CARE INSTRUCTIONS

The jacket shall have a sewn in label giving care instructions and a permanent woven size tag. The jacket shall also have a label indicating lot number, size, fiber content, and RN number.

SIZE RANGE

The jacket must be available in the following sizes:

Regular:	32 - 54 (even sizes only)
Short:	34 - 46 (even sizes only)
Long:	36 - 56 (even sizes only)
Extra-Long:	40 - 52 (even sizes only)

LIMITED WARRANTY

The sample and contract garments shall carry a manufacturer's printed warranty hang tag. A sample warranty hang tag must accompany the bid package as well. The tag shall instruct the owner of their rights under the warranty.

The limited warranty shall contain at minimum the following:

Warranty Coverage: Manufacturer agrees to warrant to the original purchaser that the product will be free from defects in materials and workmanship for a period of three years from date of purchase. This warranty also guarantees the jacket will remain waterproof for three years.

Warranty Service: Should a covered product become defective during the warranty period, simply return it to the manufacturer with dated proof of purchase. The manufacturer agrees to repair or replace at its option any item determined to be defective and will return to purchaser at no charge.

Limitations: This warranty does not cover abnormal wear and tear, nor the color fastness of fluorescent fabrics, nor damage from chemicals, fire, misuse, accident or negligence. This warranty only applies to the original purchaser of the covered product and is not transferable.

CLASS 'B' LIGHTWEIGHT JACKET AND OPTIONAL LINING

Material: 100% Nylon Oxford Weave, water repellent fabric.

Color: Forest Green

Jacket shall be a windbreaker style with a zipper front closure to the neck and plain back with shoulder straps. The front shall be constructed of two pieces on each side reaching from the bottom of the jacket to the shoulder seam. These two pieces shall be joined with welt stitched seams. Shirred elastic each side at waist for neat fit. The inside facing of the jacket shall extend from each bottom of jacket around neck where a zip-in liner can be attached. The jacket may open at the bottom on the side seams for handgun usage, closeable with Velcro.

There shall be vertical front panels that form utility side pockets. The openings shall be bartacked at top and bottom for extra strength. Two breast pleated patch pockets with flaps to button. The cuffs shall be pointed with two buttons for cuff adjustment.

The jacket shall be closed with a #5 metal style zipper with automatic lock and preshrunk tape. The zipper tape shall be compatible with outer fabric color.

The collar shall be top stitched with collar points long enough for a neat appearance.

Entire jacket shall be made in a first-class manner. Work clothing-type jacket shall not be acceptable. All loose threads shall be removed. Jacket shall be pressed with proper pressing equipment and shall be properly shaped.

There shall be permanently affixed size labels and care instruction labels.

OPTIONAL LINING:

Entire liner shall have an outer shall of 70 Denier Taffeta faced and 50 Denier Nylon Taffeta backed fabric. Shell may be of 88-count Tricot alternate.

The liner shall be full cut, long enough to properly fit jacket and should have shirt style sleeves, properly bound and safety stitched. There shall be knit wristlets at the end of each sleeve.

There shall be one right inside patch pocket. The pocket shall be bound with a proper width bias binding.

There shall be a zipper all around the outside of the liner so that the liner may be properly zipped into the jacket.

The entire liner shall be sewn with Polyester thread and shall have permanent size tag and care instruction label.

CLASS "B" CAP

The Class "B" Cap may be worn with the Class "B" uniform, coveralls, or the optional special purpose uniform as approved by the hiring authority. The cap shall be worn in a bill-forward position. The cap shall not be worn with the Class "A" uniform jacket, and must be worn/maintained in a manner so as to not bring discredit to the uniform or the department.

Material

100% Polyester, seamless front baseball cap style with mesh back or cloth back. Round top with adjustable head size. Shall favorably compare with Hanes cap.

Color

Solid black

TROOPER CAP

The trooper cap shall only be worn with approval of the warden in areas of extreme weather. Refer to the CDC Uniform Specification Handbook for the Trooper Cap specifications.

CAMPAIGN HAT

The campaign hat may be worn with the Class "B" uniform or coveralls, and is designed mainly for outside assignments as protection from the sun.

JUMPSUIT (Male / Female)

The following jumpsuit specifications have been cooperatively developed between the California Department of Corrections (CDC) and the California Correctional Peace Officers Association (CCPOA). The identified CDC authorized and approved jumpsuit shall be incorporated into the list of approved departmental uniforms, and the design specifications shall be incorporated into the CDC Uniform Specification Handbook.

DESIGN: A fully functional one-piece suit, with a bi-swing pleated back and a two-way zipper front closure (top and bottom closure). Stand type collar with Velcro closure, or utility collar with interfacing. Upper back to have gussets sewn one inch deep from shoulder to waist to allow free movement of arms. Knees shall be double reinforced with a second layer of same fabric as remainder of garment.

FABRIC: 7.5 oz. per square yard squad cloth, 65/35% polyester/cotton blend in Twill for cooler weather, and 5.8 oz., 65/35% polyester/cotton blend in Poplin for warmer weather. Shall be made using a color fast/fade resistant method to ensure its durability and long life, that it is launderable, and that it is abrasion resistant. The salient characteristics for the cloth product are as follows:

<u>CHARACTERISTICS</u>	<u>REQUIREMENTS</u>	<u>TEST METHOD</u>
Weight (ounce per sq. yard)	5.8 / 7.5 (max)	
Tensile Strength Warp/Fill	125 / 55 (min)	
Tear Strength Warp/Fill	6.0 / 4.0 (min)	
Abrasion		1000 cycles
Shrinkage Warp/Fill	3.0 / 3.0	

COLOR: Available standard colors include black and CDC approved green-olive drab.

ZIPPERS: All zippers are to be heavy-duty nylon or rust resistant material. Front zipper to be a full-length zipper with a top locking slider and a bottom non-locking slider. Pocket zippers are to utilize non-locking sliders.

NECK CLOSURE: Stand type collar with Velcro closure, or utility collar with interfacing.

WAISTBAND: Reinforced waistband in front with 1.5" wide elastic encapsulated between two layers of self material and sewn together with a minimum of four rows of chain stitching in back. Five 2.5" belt loops to accommodate heavy leather belt.

POCKETS: Two chest patch pockets, approximately 7x7.5 inches with horizontal zipper. One pen/pencil slot on left chest pocket 1" below zipper to bottom of pocket. Two (slash style) trouser pockets in front. Two rear hip patch pockets, or inserted pockets, each approximately 7" wide by 7" deep with horizontal zipper closure. One zippered calf cargo pocket on outside of the right lower leg (above boot top) approximately 7.5" wide by 9" deep with diagonal zipper closure. Two zippered thigh cargo pockets, one each on the outside of the left and right legs above the knees, approximately 7.5" wide by 9" deep with diagonal zipper closure. Cargo pockets on legs may also be of the design which opens straight across the top of the pocket with flap closures secured with hook and loop fasteners "BDU" Type.

SLEEVES: One piece, long sleeve, set-in style with 2-ply cuffs with covered snap closure, or sleeve closure tabs with hook and loop closures. Additionally, sleeves shall have shirt vents measuring no less than 5" inches. Short sleeves shall be hemmed at approximately 10 inches in length.

SEAMS/STITCHING/THREAD/EDGES: 2 or 3 ply Polyester Core, Size 40.

- A. Stitches per Inch 8-10.
- B. Bartack, 28 stitches per Bartack, $\frac{1}{2}$ +/- 1/8 inch wide.
- C. Pattern allows for 1/4 inch seams on shell and pockets and shall be 301 Stitch Type. As an alternative, 401 Stitch Type may be used for making parts and any Holding or Basting Stitch.
- D. Over-edge Stitching shall be Stitch Type 502, 503, or 504.
- E. All seams not caught by another seam shall be adequately back tacked to ensure seam integrity.
- F. Any Holding or Basting Stitch is allowed provided it doesn't show on the outside of the finished garment.
- G. All Edge Stitching shall be 1/4 inch plus or minus 1/16" T-Flaps, Lower Pockets Flaps.
- H. Top of all exposed raw edges of reinforcement and pocket material must be over-edged.

LABELING: Shall have a permanent label listing fabric type, washing instructions, lot number, size, fiber content and RN number. Label must state, "Made in USA." garment will have a TSA label sewn in at the collar, as well as a warning label that the garment is not flame resistant.

CERTIFICATION: The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this performance specification, and conforms to the producers own drawings, specifications, standards, and quality assurance practices.

ADDITIONAL INFORMATION: One badge holder located above left chest pocket with two brass or chrome rust resistant eyelets spaced vertically 1" apart. Snaps shall be all metal.

RAIN GEAR

Rain gear for outside use shall be a one or two piece raincoat or rainsuit, California green in color, or equivalent as follows:

- The one-piece raincoat is most applicable for uniform staff not assigned to long periods out-of-doors.
- The two-piece rainsuit is most applicable for uniform staff assigned to work assignments mainly out-of-doors.

The rain gear specifications shall be as follows:

Material:

- 200 Denier Nylon Oxford with 1.25-ounce Polyurethane coating on inside with a total weight of 4.5 ounces per yard; not affected by extreme temperatures, will not stiffen, crack or peel; resistant to saltwater, steam, static; treated for flame retardancy; and machine washable in cool water.
- Seams shall be felled and sealed with Polyurethane to prevent leaking; all stress points must be double stitched; thread is Dacron wrapped cotton size 20; non-conductive nylon snaps; and seams and material will withstand a minimum hydrostatic pressure mullen method test of 40 psi.
- Rain coat, three-fourths length, 42 inches long; caped back for breathability; snap shut front with storm flap for extra protection; reinforced, double stitched at stress points to prevent tearing; Velcro side opening for weapon accessibility; and underarm vents.
- Rain jacket, length, 32 inches; seamless shoulders for freedom of movement; caped back for breathability; snap shut front with storm flap for extra protection; Velcro side opening for weapon accessibility; and underarm vents.
- Rain pants, waist high, with drawstring and snap on fly; reinforced, double stitched at stress points to prevent tearing; patch pocket on back; pass-through pocket on front.
- To eliminate any water penetration incurred by stitching on, of cloth nameplates and badges, a sealing compound will be applied by the vendor.

References: Pack Trail Model #P-385 (pant), P-485 (jacket), P-585 (coat); California green in color, or equivalent.

SWEATER (Optional)

The optional sweater shall be a wooly pully sweater, 100% wool; V-neck; color: USMC olive with epaulets.

MATERNITY UNIFORMS

Uniformed female personnel may wear the special maternity uniform after the employee receives her physician's written confirmation of pregnancy and subsequent acknowledgement of the CMO. The peace officer may continue to wear this special uniform for 90 days following childbirth.

Pregnant uniformed personnel are authorized to wear a pullover maternity jumper and to alter the waist of their uniform slacks for maternity purposes. Each employee shall bear the expense of clothing construction and alteration.

The uniform blouse or shirt and slacks shall be worn under the maternity jumper. The regulation tie shall be worn in accordance with institution policy. A regulation dome badge shall be worn on the maternity jumper above the left breast

Specifications:

The following design specifications shall be adhered to in the construction of the approved maternity uniform:

- Pullover top and pull-on maternity pants shall be made utilizing McCall's Pattern, Number 7838, or equivalent.
- The pullover maternity top shall be fitted to individual comfort and shall be long enough to cover buttocks, but not exceed the fingertips in length. Flared pullover top, sleeveless, with or without pockets. If pockets are used, they shall be the hidden type in the side seams. Neckline shall be scoop.
- Pull-on maternity pants shall have maternity panel as shown in referenced McCall's pattern.
- Same fabric as used in constructing the regulation slacks.
- All sewing shall be done with 4-ply Polyester thread, forest green in color.

SPECIAL ASSIGNMENT UNIFORMS ARE AS LISTED BELOW

SPECIAL UNIFORMS- CUSTODY

Special uniforms for the custody series shall be as specified in this section. Individual garment specifications may be referred to in the CDC Uniform Specification Handbook. Items not specifically addressed within the DOM Subsection; 33020.9 or the CDC Uniform Specification Handbook are considered unauthorized.

SECURITY SQUAD AND ESCAPE DETAIL UNIFORMS

Institutions having special security squads and/or escape pursuit teams, whose duties take them into various crawl spaces, tunnels, attics, etc., shall purchase and maintain the following equipment for such assigned personnel.

Maximum of three coveralls per employee assigned to this function.

When full hard hat protection is required, round green fiberglass or plastic hats with small visor in front may be used. Aluminum hats are not authorized. One plastic hat per employee assigned to the security squad shall be purchased and provided by the hiring facility.

SAFETY HELMETS

Helmets shall be purchased as armory equipment for use by personnel in emergency situations, such as physical contact with incorrigible inmates. Helmets authorized for departmental use shall be approved by the CDC Emergency Operations Unit.

DEPARTMENTAL TRANSPORTATION UNIT UNIFORMS

Specifications shall be as follows:

- UP501 utility police style.
- Summer: Poplin.
- Winter: Gabardine twill.
- Black in color.

- Long or short sleeves.
- With the exception of the standard pockets that come with the uniform, the following additional pockets shall be standard. All pockets shall be zippered.
 - One thigh pocket; left leg only.
 - Hip or back pockets; one left, one right.
- Cloth identification label with the word "Transportation" to be secured above the right breast pocket. Specification:
 - Yellow lettering.
 - Black background.
 - One-inch tape, 1/2-inch letters.

Name Label:

- Cloth name labels with first initial and last name to be secured above the right breast pocket above the "Transportation" label. Same specifications as above.
- Belt loops shall be required on the uniform.
- State-issued, metal badge shall be the only authorized badge on the uniform.
- Boots (mandatory) as listed in DOM Subsection 33020.13.10.
- Cap as listed in DOM Subsection 33020.8.1.
- Bloused type coveralls.
 - All leather accessories shall be black; all metal accessories shall be gold in color.

FUNERAL UNIFORM

The official departmental uniform authorized for wearing at the funeral of another correctional peace officer, or any other law enforcement official, when attending in an official capacity, shall be the full Class "A" uniform. This shall, in all cases, include the draped departmental regulation dome badge.

DRAPED BADGES FUNERAL / MORNING PERIOD

The departmental regulation dome badge shall be draped in the approved manner at all correctional institutions immediately upon the determination that a correctional peace officer has been killed in the line of duty. Such draping shall continue through the day of the funeral or as deemed appropriate by the Director.

No draping of the departmental regulation dome badge shall occur for other than correctional peace officers killed in the line of duty except as authorized by the warden/regional parole administrator.

The draping of the Badge shall be a 3/4-inch wide band of black elastic cloth placed over the bottom portion of the badge, covering the number on the badge. This is the tradition of peace officers showing their unity after the tragic loss of a fellow peace officer.

HONOR GUARD UNIFORM

Each institution, at the Warden's discretion, may establish a uniformed Honor Guard for ceremonial functions. Such Honor Guard shall be attired, when performing in the Honor Guard's official capacity, as stated in this section. Honor Guard members are responsible for maintaining their own uniform, accessories, and accouterments. The Class "A" uniform shall be worn when serving in the Honor Guard at approved Honor Guard functions. Each institution shall provide/purchase the items listed as "Honor Guard Accouterments."

Due to the high visibility of personnel assigned to an Honor Guard Unit, the Honor Guard uniform, accessories, and accouterments shall be maintained and worn in excellent condition.

Prior to any use of the Honor Guard, an inspection of the unit shall be conducted by the Honor Guard Commander or his/her designee, to establish that each member is attired uniformly and will hold the Department and themselves in the highest of esteem. If weapons and/or duty belts, for example, are deemed appropriate, care must be taken to assure uniformity.

REGULATION SHIRT (HONOR GUARD)

Honor Guard members shall wear the departmental approved Class "A" shirt. The shirt will include the following:

The shirt for female Honor Guard members may be designed to include two, four, or six darts; two may be bust darts, two may be front darts, and two may be back darts, providing front and back darts are placed on the crease.

REGULATION TROUSERS / SLACKS (HONOR GUARD)

Honor Guard members shall wear the departmental approved Class "A" trouser/slacks. Trousers/slacks will include the following:

- The rear left pocket shall remain buttoned at all times. At no time shall any object be placed in trousers/slacks pockets.
- At no time will the trousers/slacks legs be bloused.

BATTLE JACKET (HONOR GUARD)

The battle jacket (dress jacket) shall be worn at the discretion of the Honor Guard Commander for approved Honor Guard functions. When designated, both male and female Honor Guard members shall wear the battle jacket.

- The battle jacket shall include all approved Honor Guard accouterments and accessories when worn.
- When utilizing the battle jacket for Honor Guard functions, the jacket shall remained zipped at all times.

ACCESSORIES - HONOR GUARD

The following departmental approved accessories shall be worn with the Honor Guard uniform:

- Badge
- Hat shield, to be worn on all approved Honor Guard hats including berets.
- Shoulder patches
- Service stripes
- Rank insignias
- Departmental awards
- Class "A" uniform hat
- Sam Browne (duty) belt, black leather with basket-weave design. Metal shall be gold in color.
- Buckle, brass or gold plated, metal only, colonial type, 2-1/4 inches wide with two tongues.
- Enclosed snapping handcuff case. Black leather with basket-weave design. Gold in color, snap. To be worn centered, in back, on duty belt.

- Four (4) black leather, basket-weave, 3/4 inch wide keepers with gold in color snaps. Keepers shall be worn, one (1) on left and one (1) on right side of handcuff case, and one (1) on left and one (1) on right side of belt buckle.

ACCOUTERMENTS

In addition to the normal Class "A" uniform, the following "Honor Guard Accouterments" shall be worn with the Honor Guard uniform:

- Ascot (bib-scarf): breakaway, rectangular in shape, the recommended color is gold, however, choice of color may be established by each institution for the Honor Guard Unit.
- Gloves: plain white, cotton and nylon blend fabric.
- Campaign hat: black in color, felt or straw. Hat Brim Cord: gold in color, worn on Campaign hats only. Each end of the cord to have a double acorn, with a single slide acorn. Both double acorns to lay on the brim and to the center-front of the crown. The single acorn to lay on the brim against the center-front of the crown.
- Beret: dark green in color, wool felt with sweatband and insignia stiffener.
- Honor Guard Epaulette: black in color with gold embroidered trim and lettering. Lettering will indicate represented institution, Honor Guard, and position held on team. Honor Guard epaulettes shall be worn on the left shoulder, shirt epaulettes. Honor Guard epaulettes may also be worn on dress, Class "A" battle jackets and shirts during normal working hours. Honor Guard epaulettes shall not be worn on Class "B" uniforms, foul weather jackets, lightweight jackets, rain gear, or coveralls.
- Aiguillette (Shoulder Cord): gold in color, nylon braided. Honor Guard Commanders and Assistant Commanders shall wear aiguilletes with three additional cords (one of which includes a brass tip). All other Honor Guard team members shall wear aiguilletes without additional cords. All aiguilletes shall be worn attached to the right shoulder epaulette of the Class "A" battle jacket or Class "A" shirt.
- Nameplate: brass or gold plated, metal only, with engraved, black, block lettering.
- Mourning Band: Refer to DOM Subsection 33020.9.6, "Draped Badges/Funeral/Mourning Period.
- Shoe Taps: to be worn on heels of shoes/boots (optional).
- Sword with scabbard: the sword represents a position of authority and shall be worn by the Honor Guard Commander and/or Assistant Commander only.

HONOR GUARD TEAM MEMBERS

- One (1) Honor Guard Commander
- One (1) Assistant Honor Guard Commander
- One (1) Rifle Team Instructor
- Seven (7) Rifle Team Members
- One (1) Color Guard Instructor
- Three (3) Color Guard Team Members
- One (1) Institutional flag Barer
- One (1) Guidon
- One (1) Communications Officer
- One (1) Quartermaster
- Two (2) Team Members

The number of members may increase should the institution elect to establish a "Drum and Bugle Corps" for taps, proper cadence and to compliment a paramilitary marching unit. If a Drum and Bugle Corps is established, the following musical instruments shall be utilized:

- One bass drum and sticks
- One triton drum unit and sticks
- Three snare drums and sticks
- Two bugles or trumpets

EQUIPMENT – (HONOR GUARD)

Due to the significant amount of ceremonial functions that the Honor Guard participates in, it is necessary for the Honor Guard to have the following equipment:

Flags

- One (1) Ceremonial flag of the United States (3' x 5') with staff, American Eagle top mount, harness (flag carrying device), and stand.

When carried in procession with another flag or flags, the Flag of the United States shall have the place of honor at the right; or, when there is a line of other flags, our national flag may be *in front* of the center of that line. At all times, every precaution

shall be taken to prevent the flag from becoming soiled. It shall not be allowed to touch the ground or floor, or to brush against objects.

When the flag is displayed from a staff projecting horizontally, the union (blue field) of the flag shall go clear to the peak of the staff.

At no time shall the Flag of the United States be dipped in salute. Other flags such as the State of California Flag, Institutional Flag, and Guidon shall be dipped "To the Color" (Flag of the United States) during the playing of the national anthem and during the "Pass in Review."

Flags of the United States used to cover caskets shall measure 5' x 9 1/2'. Each institution shall be responsible for providing this flag to the family of the deceased.

When the flag is used to cover a casket at funerals or ceremonies honoring a person deceased, it shall be placed so that the union is at the head and over the left shoulder. The flag shall not be lowered into the grave or allowed to touch the ground.

- One (1) California State flag with staff, Spear top mount, harness, and stand.
- One (1) Institutional Flag with staff, harness, and stand.
- One (1) Guidon (flag/pennant signifying specific Honor Guard Unit).

WEAPONS, AMMUNITION, AND EQUIPMENT (HONOR GUARD)

The following departmental weapons, ammunition, and equipment are approved for Honor Guard use:

- **Ruger Mini-14:** .223 (5.56 NATO) caliber. Semi-automatic, gas-operated, shoulder-fired weapon.

Ammunition: Blank.

Equipment: Magazine.

Primary use: 21-Gun Salute, Spinning maneuvers.

- **Revolver:** Smith & Wesson .38 caliber, Model 64, 4" barrel. *Note:* To be issued to the Honor Guard Commander, Assistant Commander, and Honor Guard Instructors/Leaders only.

Ammunition: .38 caliber duty ammunition.

Equipment: One (1) holster, Two (2) Comp II speedloaders with pouches.

Primary use: Self-defense.

- **Shotgun:** Remington, Model 870, 12 Gauge.

Ammunition: Blank.

Equipment: Ear protection.

Primary use: 21-Gun Salute.

Events:

- Each institution will elect four public events in their local community in which the Honor Guard will participate.
- The Honor Guard may be used for any National or State event, Department of Corrections event or other agency events as authorized by the Warden and approved by the Regional Administrator.
- The Honor Guard, with the authorization of the Warden, may perform burial ceremonies for any staff member or public figure when asked by the families or community.

The Honor Guard members will be relieved of duty and their posts covered according to the institution's policy, and when appropriate, may utilize state vehicles for transportation.

SPECIAL EMERGENCY RESPONSE TEAM (SERT) UNIFORM

The official uniform and insignia for SERT shall be that which is approved and authorized by the CDC Emergency Operation Unit (EOU), Institutions Division. The SERT uniform shall be worn by SERT members only, and only when activated for deployment or training. Contact the EOU, Institutions Division for SERT uniform designation, insignia, accessory items, and specifications.

UNIFORM HAT / CAP / TIE REQUIREMENTS – CUSTODY

On any official business where a Class "A" Uniform is required for off grounds duties, a Class "A" Hat shall be worn. For staff who are required to wear a Class "A" Uniform for duties on grounds, or who voluntarily choose to wear a Class "A" Uniform, the Class "A" Hat is optional. However, the Class "A" Hat must be available to the on duty staff member.

The Class "B" cap, the trooper cap, or the campaign hat may be worn while the employee is wearing an optional uniform. Employees authorized to wear an optional uniform shall not wear/utilize a Class "A" Hat.

It is mandatory for all uniformed staff to wear a regulation tie with the Class "A" uniform, when wearing a long sleeve shirt, or when wearing any outer garment over the shirt (long or short sleeve).

REGULATION UNIFORM FIRE CHIEF AND FIREFIGHTER

The regulation fire chief and firefighter uniforms shall be addressed in this section. Individual garment specifications may be referred to in the CDC Uniform Specification Handbook. Items not specifically addressed within this DOM Subsection or the CDC Uniform Specification Handbook are considered unauthorized.

OFFICIAL CLASS "A" UNIFORM - FIRE CHIEF

The below noted uniform shall be worn by all institution fire chiefs:

- Regulation double-breasted coat.
- Regulation trousers.
- Black leather belt 1-1/2 inches or 1-3/4 inch width with single prong tongue buckle (no decorations except official Department belt buckle or warden approved institutional belt buckle).
- Black clip-on or Velcro fastened tie.
- Round top, white vinyl, fireman's hat with insignia.
- Regulation long sleeve shirt (white).
- Black plain-toe shoes or boots (without buckles); black socks (solid color).
- Regulation Fire Chief badge; hat and collar insignia.
- Departmental Fire Service shoulder patch attached to regulation shirt and coat.
- Departmental nameplate (blue lettering on gold plate).

COAT – FIRE CHIEF

The regulation double-breasted coat specifications shall be navy blue No. 368-16 Metcalf Serge or Visa Serge (100% texturized Polyester/Dacron blend, Department approved). Double-breasted, six buttons (three each side); badge holder left side; two lower flaps (dummy pockets) with flap 2-1/4 inches deep by 3-3/4 inches wide to be in proportion to coat size. Sleeve buttons, three each sleeve; F.D. braid 1/2-inch gold; 3-1/2 inches from bottom of sleeve. Lapel to be notched; 4-1/2 inches wide; double stitched 3/8-inch. Trim to be 3-1/2 inches from bottom of sleeve; two 1/2-inch gold color strips; 1/4-inch apart.

TROUSERS

The regulation trouser specifications shall be navy blue No. 368-16 Metcalf Serge or Visa Serge (100% texturized Polyester/Dacron blend Department approved). Two back pockets; two front pockets; seven keystone loops; zipper fly; and button on left back pocket.

DRESS SHIRT

The regulation shirt shall be a white dress shirt, Flying Cross No. 5400 or equivalent, standard collar, medium points; either French cuff, barrel cuff or short sleeve optional with wearer.

HAT

The round top fireman hat specifications shall be white vinyl top; gold color braid chin strap; gilt buttons; and Holbrook embroidered flame visor.

OFFICIAL CLASS “A” UNIFORM - FIREFIGHTER

The below noted uniform shall be worn by all institution firefighters:

- Regulation battle jacket, navy blue with insignia.
- Regulation trousers, navy blue color.
- Regulation shirt, white.

- Black leather belt 1-1/2 inches or 1-3/4 inches wide with single prong tongue buckle (no decorations except official Department belt buckle or warden approved institutional belt buckle).
- Regulation firefighter hat (blue) with insignia.
- Black plain-toe shoes or boots (without buckles); black socks (solid color).
- Regulation firefighter badge and collar insignia.
- Black clip-on or Velcro fastened tie.
- Departmental Fire Department shoulder patch attached to regulation shirt and jacket.
- Departmental nameplate (blue lettering on silver plate).

A firefighter who has been designated as assistant fire chief shall wear the same uniform as the fire chief. The only difference shall be the assistant fire chief shall wear the assistant fire chief badge and display only one braid around the dress coat or battle jacket.

BATTLE JACKET – FIREFIGHTER

The battle jacket specifications shall be as follows:

- Patch pocket; industrial style, 32200 or H.S. 759.
- Jacket shall have a care label permanently affixed and also have size label showing fiber content and WPL number.
- Fabric: Milliken Mills #4936-3064; Color: navy blue; Content: 100% Polyester: Weight: 13-1/3 ounces; Weave: Elastique or equivalent.
- Waist length jacket with a zipper to the bottom of the lapel. To have peak lapels and a bi-swing back. A cloth belt is to be stitched down the back. Side adjustment straps, shoulder straps, two breast patch pockets with flaps, side body, one inside pocket, nylon lined body and sleeve, and inner vitals including shoulder pads. One badge tab and no waistband.
- Two box pleated breast pockets with flaps with Velcro at the edges of the flaps. Flaps to button with silver-gilt F.O. buttons. One inside pocket on the right side. Bi-swing two-piece back (bi-swing connected to Lastex). Sweat shields or the same material as jacket. Turn-up bottom approximately 2-1/4 inches.

- After jacket has been completely sewn and ready for pressing, it shall be pressed on both utility presses and shaping presses. All loose threads shall be removed. All proper size tags, content labels and care instructions shall be permanently affixed to the garment.
- Sleeve Piping: F. O. braid 1/2 inch silver, placed on each sleeve from seam to seam 3 inches above the cuff.

CLASS "A" AND CLASS "B" WORK AND DRESS SHIRT- FIREFIGHTER

The regulation shirt specifications shall be as follows:

- Short sleeve or long.
- White, 65% Dacron Polyester/35% Cotton.
- Shall have badge tab over the left pocket; a permanent collar stay; two plain pockets with peaked pocket flaps; and a pencil compartment on the left pocket.
- Reference: Flying Cross or equivalent.

TROUSERS (PACER) FIREFIGHTER

The uniform trouser specifications shall be as follows:

- Each regulation trouser shall bear the following label guaranteeing genuineness of the material used; "We guarantee this cloth to be 100% texturized Polyester/Dacron".
- Color: navy blue, 100% texturized Polyester/Dacron material.
- The trousers shall be made using a modified uniform pattern, having a plain front with straight side pockets and two back pockets. The front pockets shall have a minimum opening of 6 inches and shall be 5-1/2 inches by 6 inches deep from the bottom of the opening. They shall be stitched, turned, and restitched. The back pockets shall be made with a Reese PW automatic machine and shall be finished on the outside with an exposed top and bottom cord. The left hip pocket shall be button through. The front pockets shall have straight bartacks, and each back pocket shall be bartacked with a triangular bartacking machine.
- The waistband shall be a minimum of 2 inches wide and shall be closed with a crush-proof hook and eye, the eye being bartacked for stability. The waistband curtain shall have snugtex and be 65% Polyester/35% Cotton with a durable press finish and shall match the color of the pocketing. The waistband curtain twill shall have a minimum thread count of 66 x 56, and there shall be 2.90 yards per pound. It shall be attached with a rocap machine. The waistband stiffener 3/4 inches in width shall be sewn into the waistband on the front of the trouser from

side seam to side seam to prevent waistband rollover. The trousers shall have a continuous closed waistband.

- All pocketing shall be 65% Polyester/35% Cotton with press-to-last finish. The front pockets should be constructed from one piece of material with a woven reinforced area starting at the bottom and extending approximately 3-1/2 inches. From the bottom up, it shall be woven 72 x 60. Since this reinforced area assures double wear, no other type pocketing shall be acceptable. All pocketing shall be black in color.
- The right fly lining and crotch lining shall be of the same fabric and color as the waistband curtain. The right fly lining shall be sewn to the left fly below the zipper. The inside left and right flies shall be fused with an interlining for stability. A separate French fly made of the outer fabric shall be sewn to the inside right fly.
- There shall be five belt loops on waist sizes 28, 29 and 30 and a minimum of seven on all sizes over 30. The loops, shall be 2-1/2 inches wide at the top and tapering to 1-1/2 inches at the bottom. Except for the back loop, which shall be tacked on, all loops shall be sewn into the bottom of the waistband and into the rocap.
- The trousers shall be closed with a Talon 42 Nylon zipper with a memory lock slider. The zipper tape must have been treated for Durable Press finishing. There shall be a brass bottom stop at the base of the zipper chain. A straight bartack shall be sewn through from the outside of the garment to the inside at the bottom of the fly. It shall be sewn through the zipper tape, the right and left fly, and the right fly lining. The right and left fly shall be joined by an additional bartack located below the bottom zipper stop on the inside of the trouser. This bartack will reduce stress on the left fly and zipper.
- The entire trouser shall be seamed with Polyester core thread and the seat seam shall be stitched with a tandem needle seat seaming machine.
- All workmanship shall be first class structure with all loose threads removed. They shall be pressed completely and properly. Side seam, inseam, and seat seam shall be pressed open. There shall be a Texpak clip attached.
- The trousers shall have a sewn-in label giving care instructions and shall be marked with lot number, size, fiber content and WPL number.

HAT

The regulation fireman hat shall be navy blue No. 386-14, Metcalf, Wanskuk Serge. Black leatherette chin strap held by silver colored "F.D." buttons.

OPTIONAL UNIFORM – FIRE CHIEF AND FIREFIGHTER

Specifications for the optional uniform which may be worn by the fire chief and firefighters may be referred to in the CDC Uniform Specification Handbook, and include the following garments:

- Battle Jacket (Fire Chief)
- Blazer (Fire Chief)
- Trousers (Fire Chief and Firefighter)
- Light Weight Jacket (Fire Chief and Firefighter)
- Lining (Optional)
- Foul Weather Jacket (Fire Chief and Firefighter)
- Work Uniform Trousers (Fire Chief and Firefighter)
- Jacket and Raincoat (Fire Services)

BATTLE JACKET - FIRE CHIEF

The fire chief battle jacket specification for the optional uniform shall be as follows:

- Material: Navy blue No. 386-16, Metcalf Serge or Visa Serge (100% texturized Polyester/Dacron blend Department approved).
- Jacket shall be Eisenhower style, waist length of approximately 21-3/4 inches on a size 40, and have peak lapels. The inside of the jacket shall contain shoulder pads, sleeve heads, chest piece inner front, armhole tape and cuff inner lined. The entire body and sleeve shall be fully lined.
- 180-count Rayon Satin, pre-shrunk lining shall be colorfast and perspiration resistant.
- Front shall be plain with box pleated patch pockets, flaps, shoulder straps and badge tab. Inside facing of jacket shall be the same as the outer fabric. The front shall be zipper front with a zipper no less than 14 inches long. The back shall be seamed (two-piece back) bi-swing, ends of each bi-swing held in place with a strip of elastic. There shall be a separate waistband cut in two pieces, and the waistband shall be approximately 2-1/2 inches wide with the adjustable straps on each side over hips.
- The sleeves shall be standard coat style, set in, and shall have a 2-inch hem. The bottom of the sleeve shall have an inner lining. Two sleeve buttons shall be gold colored fire chief bugles.

- There shall be two outside box pleated patch pockets measuring approximately 5 inches wide and 6 inches deep, and there shall be scalloped flaps.
- Collar shall be properly inner-lined and under collar properly shaped.
- Shoulder strap shall be made of the same fabric as the jacket and shall be sewn into the sleeve seam, cross-stitched, and the end of the shoulder strap tacked to the jacket at the neck.
- Badge tab shall be made of the outer fabric, be 3/4-inch wide with two eyelets spaced vertically 1-inch apart (center to center), and the badge tab shall be centered above the left flap. Two, 1/2-inch gold stripes, 1/4-inch apart.

BLAZER – FIRE CHIEF

The blazer specifications shall be as follows:

- Fabric: grey - 100% texturized Polyester.
- Form fitting classic-style jacket, long sleeve, two button front single breasted with soft shoulders. There shall be two 1-inch welted pockets just below the waistline with flaps. The back shall be plain with a center vent.
- All sewing shall be done with Polyester core thread.
- Tailored with good quality, matching lining with coat fronts, employing standard practices used in coat construction. For shape retention, the collar and front facing shall be interlined with heavy "armo", "hypo" or pellon-type fabric.
- Regular coat style sleeves set in with single needle having a minimum 2-inch hem for alteration. Two sleeve buttons shall be gold colored Fire Chiefs bugles.
- Two patch-type pockets just below the waistline. One patch-type pocket over left breast.
- There shall be a departmental Fire Department shoulder patch sewn onto the breast pocket.

TROUSERS – FIRE CHIEF AND FIREFIGHTER

The trousers specifications shall be the same as Firefighter Class "A" trousers.

LIGHT WEIGHT JACKET – FIRE CHIEF AND FIREFIGHTER

The light weight jacket specifications shall be as follows:

- Fabric: 100% Nylon Oxford Weave, water repellent.
- Color: Navy blue.
- Windbreaker style with a zipper front closure to the neck and plain back with shoulder straps.
- The front shall be constructed of two pieces on each side reaching from the bottom of the jacket to the shoulder seam. These two pieces shall be joined with welt stitched seams. Shirred elastic each side at waist for neat fit. The inside facing of the jacket shall extend from each bottom of jacket around neck where a zip-in liner can be attached. The jacket may open at the bottom on the side seams for handgun usage, closeable with velcro.
- There shall be vertical front panels that form utility side pockets. The openings shall be bartacked at top and bottom for extra strength. Two breast pleated patch pockets with flaps to button. The cuffs are to be pointed with two buttons for cuff adjustment.
- Shall be closed with a No. 5 metal style zipper with automatic lock and pre-shrunk tape. The zipper tape shall be compatible with outer fabric color.
- The collar shall be top-stitched with collar points long enough for a neat appearance.
- Shall be made in a first-class manner. Work clothing-type jacket will not be acceptable. All loose threads shall be removed. Jacket must be pressed with proper pressing equipment and shall be properly shaped.
- There shall be permanently affixed size and care instruction labels.
- References: Fechheimer Bros. No's 42155, 42156 and 42166, Horace Small No. 2503, or equivalent.

LIGHT WEIGHT JACKET— LINING (OPTIONAL)

The optional lining specifications shall be as follows:

- Fabric: Entire liner shall have an outer shell of 70 Denier Taffeta-faced and 50 Denier Nylon Taffeta-backed. Shell may be of 88-count Tricot alternate.
- The liner should be full cut, long enough to properly fit jacket and should have shirt style sleeves, properly bound and safety stitched. There shall be knit wristlets at the end of each sleeve.
- There shall be one right inside patch pocket bound with a proper width bias binding.
- There shall be a zipper all around the outside of the liner so that the liner may be properly zipped into the jacket.
- Shall be sewn with Polyester thread and have permanent size and care instruction label.
- References: Fechheimer Bros. No. 32704, Horace Small "C", or equivalent.

FOUL WEATHER JACKET - FIRE CHIEF AND FIREFIGHTER

The foul weather jacket specifications shall be as follows:

- Fabric: 100% Nylon super twill.
- Color: Navy blue.
- Body and sleeve shall be lined with 1/4-inch polyform quilted to 70 Denier Nylon Taffeta-faced with nonwoven back, or to 88-count Nylon Tricot.
- Borg 1/2-inch Orlon Pile for the top collar. The under collar shall be of the same fabric as the outer shell and the collar shall be interlined. Collar shall be attached so there is a clean edge. There shall be a storm flap made of this outer fabric.
- Concealed zipper front, waist or 3/4 length separate waistband, five-button front and shoulder straps. Buttons to reflect either Firefighter scramble or Fire Chief's bugles.
- Coat style sleeves. The bottom of sleeves shall be interlined with nonwoven fabric. There shall be concealed wristlets at the bottom of the sleeves. The bottom of the sleeve shall be vinyl bound 1/4-inch to shell.

- There shall be two box pleated patch pockets finished approximately 6-1/2 x 7 inches, with three-pointed scalloped flaps and snap fasteners at each corner. The flaps shall have a firm interlining. Pockets shall have a firm interlining covered with Polycotton so as to create a hand-warmer pocket with an opening of approximately 5-3/4 inches on each side. The patch pockets shall be double stitched to the garment and the left breast pocket shall have a pencil compartment with an opening through the top of the flap. There shall be two pockets, one on the left side and one on the right side. All pocket flaps shall be interlined and flaps shall be bartacked at both ends.
- There shall be a badge tab of the outer fabric approximately 3/4-inch wide with two metal eyelets spaced vertically 1-inch apart and centered 2-1/2 inches above the left pocket flap.

WORK UNIFORM TROUSERS - FIRE CHIEF AND FIREFIGHTER

The work uniform trousers specifications shall be as follows:

- Material: 65% Polyester/35% Cotton, 8-ounce Twill with Soil Bar (or Nomex).
- Color: Navy blue.
- Shall be made using a uniform pattern having a plain front with Quarter-top pockets, watch pocket, 3/4 inch drop belt loops, waistband curtain with Ban-rol or equivalent.
- References: American Mode (No. 8827-8829), Walking Tall (No. 9949) or equivalent.

JACKET AND RAINCOAT - FIRE SERVICES

The jacket shall be Lee, navy blue color, 65% Dacron Polyester/35% cotton. Matches trousers, patch pockets. Liner--optional.

The raincoat shall be a long black, navy style with detachable lining.

The Class "B" cap specifications shall be as follows:

- Material: 100% Polyester. Seamless front baseball style cap with mesh or cloth back. Round top with adjustable head size. Black in color.
- Shall favorably compare with the Hanes cap.
- Insignia: Fire Chief's bugles or Firefighter's scramble.

THE CAP:

- Shall be worn in a bill-forward position.
- Shall not be worn with the Class "A" jacket.

Shall be worn in a manner so as not to bring discredit to the uniform or the Department.

UNIFORM ACCESSORIES

Only approved accessories and equipment as described in this section shall be worn on or with the uniform.

DEPARTMENTAL AWARDS

The Department has authorized the awarding and wearing of medals and ribbons to correctional peace officers, both individual and unit awards, as stated and explained in DOM Section 31030 of this manual. These awards, in the order of their seniority, are: The Medal of Valor; The Corrections Star (Gold); The Corrections Star (Silver); The Corrections Star (Bronze), The Distinguished Service Medal; and the Unit Citation. Nondepartmental awards and citations may be worn, upon approval of the warden.

Awards shall be worn on the Class "A" jacket as follows:

- One-quarter inch above the right breast pocket. The regulation nameplate shall be placed 1/4-inch above the award(s).
- If one award ribbon is worn, it shall be centered on the pocket between the regulation nameplate and the pocket.
- If two award ribbons are worn, they shall be placed end-to-end with the senior ribbon to the inside and centered on the pocket between the regulation nameplate and the pocket.
- If three award ribbons are worn, they shall be placed end-to-end with the senior ribbon to the inside and centered on the pocket between the regulation nameplate and the pocket.
- If four award ribbons are worn, there shall be one row of three ribbons on the bottom as above. The fourth ribbon, most senior, shall be placed singularly and centered above the row of three ribbons with the regulation nameplate 1/4-inch above it. The two rows of ribbons shall be 1/8-inch apart.

- If five award ribbons are worn, there shall be one row of three ribbons on the bottom and one row of two ribbons centered on the top. They shall be 1/8-inch apart with the regulation nameplate 1/4-inch above them.
- If six medals are worn, there shall be one row of three medals on the bottom and one row of three medals on the top. They shall be 1/8-inch apart with the regulation nameplate 1/4-inch above them.
- The complete set of ribbons and the order of their placement on the Class "A" jacket is as illustrated.
- State Medal of Valor Pin, 25-Year Service Pin, and other state service/award pins shall be worn only on the Class "A" jacket and shall be centered, 1/4-inch above the nameplate. If two pins are worn, they shall be centered 1/4-inch apart and 1/4-inch above the nameplate.
- The service emblem, employee organization pin, and the Safety Award Pin may be worn as a tie pin. Other tie pins or tie clasps may be worn but shall be small and plain without stones or other decorations. They also shall be gold in color in keeping with the gold color of all other metal accessories. Tie pins depicting handcuffs, pigs, guns, etc., shall not be worn.

HAT SHIELDS

The hat shield worn by correctional officers, correctional sergeants, correctional lieutenants, correctional captains, and facility captains shall be as follows:

- Blue soft enamel lettering.
- Gold-plated center seal of the State of California.
- Base material of back shall be 16 gauge brass.
- Single screw back with one anchor pin.
- The words, "State Department of" shall encircle the state seal with the word "of" centered at the base of the 3/32-in Gothic lettering. The word "Corrections" shall be centered across the width of the base in 1/8-inch Gothic lettering.

The hat shield worn by the fire chief shall be five crossed trumpets on gold plated 1-1/2 inch diameter round backing. Single screw with one anchor pin (Blackington No. A2811).

The hat shield worn by firefighters shall be a Maltese cross on nickel plated 1-1/2 inch high and 1-1/2 inch wide round backing. Ribbon at the top of the circle with "Firefighter"

in blue Gothic lettering. Circle with fireman's scramble (hat, ladder, axe, pick, pole and trumpet). Lower tip to have the word "California" with the "f" on the left side and the "O" on the right side. Single screw with one anchor pin (Blackington No. 8501).

DEPARTMENTAL SHOULDER EMBLEMS

The following described insignias have been adopted as the departmental emblems and shall be used as the departmental shoulder patches.

All uniformed correctional peace officers shall wear the shoulder patch described below.

(CORRECTIONAL PEACE OFFICERS)

The shoulder patch shall be in the shape of a shield with the words "California Department of Corrections" above the state seal.

The shoulder patch shall be 3-5/8 inch by 4-1/2 inch. Background material shall be 7-1/2 ounce Cotton twill, mercerized and sanforized. Material count to be 88 by 42, first quality and no milling ends or finishing seconds. Material shall be certified washable by the American Institute of Laundering.

Colors shall be as shown on the detail below:

- The patch shall be embroidered. Thread shall be Rayon yard, not to exceed 150/2 Denier, and shall be first-quality continuous filament, regenerated cellulose type, colorfast and approved by the American Institute of Laundering. Bobbin thread shall be Nylon.
- Border stitching shall be applied to emblems after loom operation. Border shall consist of seven separate threads, including five 105/2 Denier Rayon yarn for top portion and two 3-cord mercerized cotton threads for underneath or back side of emblem. Edge density shall be at least 26 per inch. End threads of border shall be pulled tight and secured to back side of emblem by a nontoxic adhesive.
- The shoulder patch shall be attached on the left and right sleeves of all uniform coats, jackets, shirts, and coveralls (except rain gear). The top of the patch to be 1/2-inch below the sleeve head seam and in such a manner that a line bisecting the center of the patch shall be perpendicular to the ground when the garment is worn. Shall be sewn on garment with colorfast medium gold thread, not cross stitched.
- Shoulder patches shall be kept in good condition. When no longer in good condition, shoulder patches shall be replaced.

NOTE: Department shoulder patches are stocked by local uniform vendors. Employees shall purchase their shoulder patches.

FIRE SERVICE EMPLOYEES

Every fire service employee shall wear the Fire Department shoulder patch described below.

The Fire Department shoulder patch shall be in the shape of a shield and shall be 3-5/8 inches by 4-1/2 inches.

Background material shall be 7-1/2 ounce Cotton Twill, mercerized and sanforized. Material count to be 88 by 42, first quality and no mill ends or finishing seconds. Material shall be certified washable by the American Institute of Laundering.

Background shall be royal blue with all lettering and patch border shall be gold. Colors shall be as shown on the detail below:

Embroidery: The words "California Department of Corrections" in gold on top of an eight-pointed cross formed by four arrowheads joining at their points with the colored State of California seal in the center. The cross and seal shall have red borders. The words "Fire Department" in gold at the bottom of the patch.

Border stitching shall be applied to emblem after loom operation. Border to consist of seven separate threads, including five 150/2 Denier Rayon yarns for top portion and two 3-cord mercerized cotton threads for underneath or backside of emblem. Edge density shall be at least 26 stitches per inch. End threads of border shall be pulled tight and secured to back side of emblem by a nontoxic adhesive.

Emblem shall be sized with a nontoxic harmless sizing that firmly welds the buckram and bobbin threads directly to embroidery and background material.

The shoulder patch shall be attached on the left and right sleeves of all uniform coats, jackets, shirts, and jumpsuits. The top of the patch to be 1/2 inch below the sleevehead seam and in such a manner that a line bisecting the center of the patch would be perpendicular to the ground when the garment is worn. To be sewn on garment with colorfast medium gold thread, not cross-stitched.

Shoulder patches shall be kept in good condition. When no longer in good condition, shoulder patches shall be replaced.

Individual employees shall be responsible for the purchase of his/her shoulder patches except for those on the Nomex wear, which the institutions shall provide.

NAMEPLATE

All uniform personnel and other personnel, who have direct contact with inmates, teachers, counselors, cooks, nurses, etc., shall wear and clearly display a nameplate.

Nameplates shall be phenolic engraving stock 3 inches long by 3/4-inch wide by 3/32-inch thick with white letters on black stock. The corners may be slightly rounded to protect the wearer's clothing. The name letter size shall be 1/4-inch high and shall be composed of the first initial of the first name, followed by a space, followed by the entire last name, centered both top to bottom and side to side. Regulation nameplate shall be worn on the outer garment unless exception is made by the warden.

Fire Chief nameplate shall be white lettering on black plate.

Firefighter nameplate shall be white lettering on black plate.

EXCEPTIONS

Fireservice employees may be allowed to have a Maltese or EMT insignia on the left side of their nameplate, if they qualify for them.

A job steward/board member may add that title to the nameplate as has been the practice (illustrated below). The cost shall be incurred by the employee. The lettering size of such title shall be 1/8-inch high. When placed on the nameplate, the grouping of name and title shall be centered both top to bottom and side to side.

SERVICE STRIPES

Service stripes shall be worn on the left sleeve of the Class "A" jacket and on the left sleeve of the long sleeve shirt. Service stripes shall be affixed 3/4-inch above the departmental stripe of the jacket and 3/4 inches above the cuff of the shirt. One service stripe shall be worn for each three years of service as a correctional peace officer.

Service stripes shall be gold thread sewn to a black felt material background with a heat-seal treatment on the back.

The overall size of each service stripe is approximately 3/8-inch by 2 inches.

Service stripes shall be sewn on the garment with black thread sewn along the border of the stripe. Service stripes on the jacket shall be placed as below, centered between the seams on an approximately 30-degree angle. Service stripes on the jacket shall be placed as below fully in front of the sleeve crease on an approximately 30-degree angle.

MALTESE CROSS

For each five years of service with the Department, uniformed fire service employees shall wear a Maltese cross on the left sleeve of the Class "A" jacket and on the left sleeve of the long sleeve shirt. The crosses shall be affixed 3/4-inch above the departmental stripe of the jacket and 3/4-inch above the cuff of the shirt in horizontal row(s).

RANK INSIGNIA

Collar rank insignia worn by correctional captains, correctional lieutenants, correctional sergeants, and fire chiefs and institution firefighters shall be affixed 1/2-inch and parallel from the inner edge of the collar. The bottom edge of the insignia shall be 1-inch from the collar point. Acting sergeants shall wear collar rank insignia only.

Correctional captains shall wear double bars, gold color, approximately 3/4-inch by 3/4-inch (Vanguard #95 Captain, or equivalent).

Correctional lieutenants shall wear single bar, gold color, approximately 1/4-inch by 3/4-inch (Vanguard #115 Lieutenant, or equivalent).

Fire chiefs shall wear five crossed trumpets, gold color on 7/8-inch round backing (Everson-Ross No. F-4028, Blackington No. A2871, Darley and Company No. G-469, or equal).

Firefighters shall wear fireman's scramble, silver color on 7/8-inch round backing. Single or double-clutch clasp (Blackington No. 3029).

Correctional sergeants shall wear sergeant chevrons, police style, gold color metal, 5/8-inch high by 3/4-inch wide with clasps (Vanguard #21 Sergeant, or equivalent).

Rank insignia worn on the epaulets by correctional captains, and correctional lieutenants shall be affixed 1-inch in from the outer edge of each shoulder seam of the regulation jacket or coat.

Correctional Captains shall wear double bar, gold color, approximately 1-inch by 1-inch (Vanguard #34 Captain).

Correctional lieutenants shall wear single bar, gold color, approximately 3/8-inch by 1-inch (Vanguard #34 2nd Lieutenant).

SLEEVE CHEVRONS CORRECTIONAL SERGEANT

Correctional sergeant chevrons shall be worn on each sleeve of the uniform jacket, and short and long sleeve shirt. Chevrons shall be three gold stripes on a black background of cotton twill, 3-7/8 inches from top to bottom, 3-1/8 inches wide. The interlocking stitch, 700 for each stripe, and the stripe shall be vat dyed Y-2-gold. The backing shall be of 28 x 24 Crinoline. The chevron shall be placed with the tip of the chevron 1/2-inch from the bottom of departmental shoulder patch. The chevron shall be sewn with black thread with professional skill.

REGULATION TIE

The regulation tie specifications shall be as follows:

- Solid black only, no design or decorative texture.
- Smooth surfaced, dry clean only fabric.
- Not to exceed 18 inches in length, or to fall below the belt line.
- Clip-on fastener or Velcro fastener types only. Tie shall not be square cut on bottom.
- References: Broome 455-BO-3, or equivalent.

The Regulation Tie is optional when wearing the Class 'B' uniform or when wearing an outer jacket or sweater.

The Regulation Tie shall be worn when wearing a Class 'A' Uniform.

OFFICIAL DEPARTMENTAL BELT BUCKLE

An official Department belt buckle has been approved by the Director. This buckle is the only buckle that may be worn in place of the standard belt buckle other than the warden approved institutional belt buckle. The approved departmental buckle approximates: 2 x 3 inches, rectangular in shape, with rounded corners per reproduction

REGULATION SHOES

MALE:

Male employees may wear shoes or boots that meet the following general specifications as items of the regulation uniform:

- Black leather, plain toe, conservatively designed. No buckles. No design in the leather, shall be smooth texture.
- In addition to the plain toe, the toe design shall be round without a bead encircling the toes.
- Shall approximate dress military styling. Shoes shall be shined at all times.
- Heel not to exceed 1-1/2 inches in height.
- No tennis shoes, cowboy, engineer or logger-style boots.

References: Boots: Acme 9080, Rocky 5066; shoes: Rock 2025; Thorogood 1267, 1253; or equivalent.

FEMALE:

Female employees may wear shoes or boots that meet the above general specifications

- Pump heel allowed, not to exceed 1-1/2 inches in height.

References: Boots: Acme 610; Shoes: Rocky 115; or equivalent.

MISCELLANEOUS ACCESSORIES FOR UNIFORM STAFF

The below specified accessories may be worn with the regulation uniform as appropriate:

- Sam Browne belt, black with basket-weave design. Metal shall be gold in color.
- Key pouches/clips, gold in color, when available, only State issue. Chains or lanyards are not permitted.
- Enclosed snapping handcuff case. Black with basket-weave design.

- Flashlight holder shall be ring type on black leather. Metal shall be gold or black in color.
- Side handle baton holder shall be ring type on black leather. Metal shall be gold or black in color.
- Whistle gold in color, metal only.
- Flashlight shall be black in color, either mini-mag, or 3 "C" or 3 "D" cell batteries only.
- Gloves shall be smooth black leather only with no "cut-outs". Both the body of the gloves and the fingers shall remain intact. No alteration of the gloves shall be permitted. Wrist high to 2 inches above the wrist in length. May be lined for warmth. Shall approximate the reference in appearance. References: Damascus #302, or equivalent.
- Load Bearing Suspenders shall be black in color and may be worn with the Class 'B' uniform. The Load Bearing Suspenders can be worn with the Class 'A' uniform in emergency situations.

No other accessories shall be worn while in uniform without the approval of the warden. There shall be no pipe holders, tobacco cases, glass cases, or other holders worn on or carried on the belt or affixed to the uniform except as approved by the hiring authority.

DEPARTMENTAL BADGES

In accordance with the requirements of Penal Code (PC) Section 830.10, the Director has ordered the wearing and possession of the approved departmental regulation dome badge by all uniformed peace officer staff, with the exception of fire department peace officer staff. Uniformed staff includes, all part or full-time Medical Technical Assistant (MTA) and custody classification employees; where CDC considers the uniform as part of their job description.

All uniformed staff shall wear the regulation badge on the outer garment at all times while on duty unless exception is made by the Warden. Uniformed fire department peace officer staff shall wear the regulation fire shield in lieu of the regulation dome badge. Nonuniformed staff designated as peace officers shall possess the approved departmental flat badge.

REGULATION DOME BADGE

The Department shall purchase and provide to each uniformed peace officer employee, through the Richard A. McGee Correctional Training Center (CTC), a numbered regulation domed badge upon the employee's successful completion of the Department's preservice academy training.

REGULATION FIRE SHIELD

The Department shall purchase and provide to each uniformed fire department peace officer employee, through the CTC, a numbered regulation fire shield upon the employee's successful completion of the Department's preservice academy training.

FLAT POCKET BADGE

The Department shall purchase and provide each nonuniformed peace officer employee, through the CTC, a numbered flat pocket badge upon the employee's successful completion of the CDC's preservice academy training.

OPTIONAL BADGE

All permanent uniformed employees may purchase a second, optional dome badge that meets departmental specifications if they so desire but shall bear the cost of the second badge. The optional badge shall bear the same number as the state issued badge.

All uniformed employees may purchase, at their own expense, a flat pocket version of the state-issued badge. The optional flat badge shall bear the same number as the state-issued regulation dome badge.

All orders for optional badges purchased at the employee's expense shall be placed through the departmental badge coordinator located at the CTC, via the institutional badge coordinator.

PAROLE AND COMMUNITY SERVICES DIVISION (P&CSD)

The P&CSD shall provide special badges to all parole agents and parole administrators. The P&CSD shall provide all custodial employees assigned to community correctional centers with a flat version of the special badge in lieu of the departmental regulation dome badge.

TEMPORARY BADGES

Badges that were being utilized at the institution and worn by staff on special assignments shall be retained by the institution as extra badges and loaned to employees in the event of a loss of, or damage to, the employee's state-issued badge. The Department shall purchase badges from the designated vendor.

SPECIFICATIONS

All uniformed personnel and nonuniformed employees designated as peace officers pursuant to California Code of Regulations (CCR) Title 15, Division 3, Section 3291(b), shall receive a departmental badge in accordance with the following specifications:

- Seven-point star badge (2-5/8 inches point-to-point).
- Gold plated. Base material and back to be 16-gauge bronze.
- Center seal of the State of California in full enamel color, 3/4-inch across.
- One-fifteenth inch blue enamel border surrounding the seal with the words "The Great Seal of the State of California" in gold letters.
- One-eighteenth inch wide indentation around the above mentioned border, gold.
- Three-sixteenth inch gold border surrounding indentation with words "California Department of Corrections" in 3/32-inch blue Gothic lettering, so centered as to leave room for 6-digit badge number on bottom of border.
- One-sixteenth inch smooth border around outer edge of badge points.
- Exposed portion of star points to be embossed with decorative design.
- One-fourth inch wide ribbon extending over bottom star point half way into left and right points. One and five-eighths inches long in gold with blue 3/16-inch lettering designating appropriate classifications.
- Vertical pin clasp on back 1-7/8 inches long.

CORRECTIONAL OFFICER

Same as described above, excluding ribbon of rank.

FIRE CHIEF

The institutional Fire Chief shall receive a badge in accordance with the following specifications.

- Shield configuration, with eagle at top.
- Three-inches in height.
- Two-inches in width.
- Gold-tone (Hi-glo) base material and back to be struck from 12-guage material for badge and 16-guage material for ribbons. Base material used will have golden color throughout and will require polishing and clear coating for durability, no surface plating required.
- Entire background of shield to be matte texture.
- Center seal of the State of California in full enamel color, 3/4-inch across.
- One-fifteenth inch blue enamel border surrounding the seal with the words "The Great Seal of the State of California" in gold letters.
- Two-sixteenth inch wide gold border surrounding above-mentioned seal with the words "California Department of Corrections" in 3/32-inch blue gothic lettering.
- One-sixteenth inch rope border around outer edge of shield.
- One-fourth inch wide and one and three-eighths inches long gold ribbon centered above state seal with blue three-sixteenth gothic lettering designating the appropriate classification.
- One-fourth inch wide and one and one-fourth inches long gold ribbon centered over above-mentioned ribbon with blue three-sixteenth gothic lettering, if needed for additional designation of classification.
- Five-sixteenth inch wide and one and three-fourth inches long gold ribbon extending in the center over the bottom of the shield with the words "Corrections Fire Department" centered on two lines in blue gothic lettering.

- One-fourth inch wide and five-eighths inch long gold ribbon centered over the bottom point of the shield inside rope border to contain up to 6-digit badge number in blue gothic lettering; centered on ribbon.
- Heavy pin, joint, and catch (#65 and #105 joint and pinstem) fitted vertically on the back of the shield, 1-7/8 inches long.
- Badges to be polished and coated with clear lacquer finish front and back to preserve finish.
- Each finished badge, including clasp on shield badge shall weigh not less than 11 ounces.

FIRE CAPTAIN / FIRE SERVICES TRAINING SPECIALIST

The institutional Fire Captain/Fire Services Training Specialist shall receive a badge in accordance with the following specifications.

- Shield configuration, with eagle at top.
- Three-inches in height.
- Two-inches in width.
- Nickel-tone (Rho-glo) base material and back to be struck from 12-guage material for badge and 16-guage material for ribbons. Base material used will have nickel color throughout and will require polishing and clear coating for durability, no surface plating required.
- Entire background of shield to be matte texture.
- Center seal of the State of California in full enamel color, 3/4-inch across.
- One-fifteenth inch blue enamel border surrounding the seal with the words "The Great Seal of the State of California" in nickel letters.
- Two-sixteenth inch wide nickel border surrounding above-mentioned seal with the words "California Department of Corrections" in 3/32-inch blue gothic lettering.
- One-sixteenth inch rope border around outer edge of shield.
- One-fourth inch wide and one and three-eighths inches long nickel ribbon centered above state seal with blue three-sixteenth gothic lettering designating the appropriate classification.

- One-fourth inch wide and one and one-fourth inches long nickel ribbon centered over above-mentioned ribbon with blue three-sixteenth gothic lettering, if needed for additional designation of classification.
- Five-sixteenth inch wide and one and three-fourth inches long nickel ribbon extending in the center over the bottom of the shield with the words "Corrections Fire Department" centered on two lines in blue gothic lettering.
- One-fourth inch wide and five-eighths inch long nickel ribbon centered over the bottom point of the shield inside rope border to contain up to 6-digit badge number in blue gothic lettering; centered on ribbon.
- Heavy pin, joint, and catch (#65 and #105 joint and pinstem) fitted vertically on the back of the shield, 1-7/8 inches long.
- Badges to be polished and coated with clear lacquer finish front and back to preserve finish.
- Each finished badge, including clasp on shield badge shall weigh not less than 12 ounces.

CONTROL OF BADGES

Due to the inherent threat to departmental security and the possible unlawful uses of peace officer badges, strict controls shall be maintained regarding departmental accountability and employee responsibility in the issue, use, and maintenance of departmental badges.

It is unlawful for any person, including employees of the Department not employed in a peace officer class, unless temporarily assigned to perform peace officer duties, to wear, exhibit, use or otherwise possess a departmental badge or a facsimile thereof without specific authority to do so.

RESPONSIBILITY

Departmental employees possessing state-issued or personal optional badges shall be held specifically responsible for the proper use and control of these badges. Loss or damage of departmentally-issued badges, loss of optional badges resulting from employee negligence or willful failure to report loss of state-issued or optional badge shall be cause for adverse action.

LOST OR STOLEN

In the event that a state-issued or optional departmental badge is lost or stolen or the badge is damaged, the employee responsible for the badge shall submit a detailed written report of the circumstances within 24 hours of the discovery. The report shall be submitted to the senior administrator of the Department facility to which the employee is assigned. P&CSD staff shall submit the report to the regional administrator. Headquarters staff shall submit the report to the Chief, Institution Services Unit.

The senior facility administrator, upon knowledge that a badge has been lost or stolen, shall:

- Cause a notice to be placed at the entrance gates of all institutions and copies of the notice to be mailed to local law enforcement agencies and the Richard A. McGee Correctional Training Center. The notice shall contain the badge number and whether it was a state-issued or optional personal badge.
- After investigating and considering facts submitted, make a determination whether the badge shall be replaced by the Department or the employee, and whether the loss or damage was due to negligence of the responsible employee.
- Take appropriate action as indicated by the circumstances revealed during the inquiry.
- Require the facility's procurement officer to order a replacement badge with a new number from the Training Center if it is determined that replacement will be made by the Department.

If it is determined that a badge is to be replaced at the expense of the employee, the employee shall submit a check for the replacement cost to the facility's procurement officer. Replacement costs are listed in the badge order form.

NOTE: These procedures for replacement in no way restrict the Department facility from temporarily lending the responsible employee a badge until a replacement badge is delivered to the facility.

DAMAGED

Damaged badge replacements will be ordered with the same numbers as the original state issued badge and the damaged badge shall be forwarded to the Training Center for destruction.

Replacement of state-issued badges shall not be done until after a 30-day period to determine if recovery of the badge is possible.

CANNOT BE RECOVERED

If lost or stolen badges cannot be recovered, the badge's number will be retired and notices of this fact shall be distributed to all institutions and local law enforcement agencies and the Training Center.

Replacement badges in such cases shall be issued, with different numbers by the Training Center.

Lost or stolen optional badges shall not be replaced by the Department. The employee, however, retains the right to submit a claim through the established Board of Control procedures if circumstances warrant. Authorization to replace a lost or stolen optional badge may be withheld by the warden if such loss was as a result of negligence in exercising proper control over the badge. Replacement may be permitted, at the expense of the employee, after a 30-day waiting period.

Employees shall not sell or otherwise transfer their badge to any other person.

PROCEDURE FOR ISSUING BADGES

Headquarters shall issue two documents allotting badge numbers to the Richard A. McGee Correctional Training Center.

The administrator of the Training Center shall establish and maintain an accurate and automated record of all departmental badges issued to peace officer employees. The Training Center shall issue a badge number to each qualified employee in the peace officer classification, according to the blocks of numbers allotted to each rank group.

Once a peace officer employee is assigned a badge number, they shall retain said number throughout their departmental career.

All peace officer employees receiving promotions or transfers to another Department facility shall retain their state-issued badge. The receiving Department facility shall have the ribbon of the employee's promotional rank, if appropriate, affixed at the bottom of the badge. The receiving Department facility shall have the ribbon of the employee's promotional rank, if appropriate, affixed at the bottom of the badge. The institution or other Department facility shall issue the employee a temporary badge until the original badge is received from the vendor with the appropriate ribbon of rank affixed. The original badge shall then be returned to the employee.

OPTIONAL BADGES

Peace officer and correctional administrative staff transferring on promotion or promoting within their current facility who have purchased optional badges shall retain the badge. They may, at their discretion and expense, have the appropriate ribbon or rank affixed to their optional badge.

TERMINATION OF STATE SERVICE

All correctional peace officers terminating state service shall surrender their state-issued badge to the Department facility processing the termination. The returned badge shall be retained by the facility to be placed in the institution loaner badge file.

RETIREMENT FROM STATE SERVICE

Correctional peace officers retiring from state service may request a retired state-issued badge upon approval of such retirement. The Department facility processing the retirement shall provide for the placement of a "RETIRED" ribbon on the state-issued badge. Retiring employees not desiring to retain the state-issued badge shall return the badge to the Department facility processing the retirement. The returned badge shall be placed in the institution loaner badge file.

REGULATION UNIFORM – MTA SERIES

MTAs and Senior (Sr) MTAs shall wear the uniform specified in the appropriate DOM article/section and this uniform specification handbook. In cases of specialty areas (such as surgery or administration), the individual institution may specify other dress codes.

LONG/SHORT SLEEVE SHIRT

Regulation Class 'B' long/short sleeve shirt; Silver-tan tropical; to be worn closed and tucked into trousers:

- Refer to Class 'B' Shirts – Male, pages 29-34 of this handbook
- Refer to Class 'B' Shirts – Female, pages 41-45 of this handbook

MTA REGULATION TROUSERS

CDC approved olive-green Class 'B' Cargo Pant:

- Refer to Class 'B' Cargo Pant – Male, pages 38-40 of this handbook
- Refer to Class 'B' Cargo Pant – Female, pages 49-51 of this handbook

MTA UNDERGARMENTS MALE/FEMALE

Undershirts

Must be T-shirt style, solid white in color, and of a smooth finish. No designs or other colors are permitted. No fish net or other ventilated styles are permitted.

Socks

Solid black in color. No designs are permitted.

MTA JACKET

The MTA Jacket shall be conservative in style and color. The MTA's may also use the departmental approved jacket and sweater:

- Refer to Class 'B' Lightweight Jacket, page 65 of this handbook
- Refer to Class 'B' Sweater, page 70 of this handbook

FOUL WEATHER JACKET

The MTA foul weather jacket shall be conservative in style and color. . The MTAs may also use the departmental approved foul weather jacket:

- Refer to Class 'B' Non-Water Proof Jacket, pages 52-54 of this handbook
- Refer to Class 'B' Non-Water Proof $\frac{3}{4}$ Length Jacket, pages 55-58 of this handbook
- Refer to Class 'B' Water Proof Foul Weather Jacket, pages 59-64 of this handbook

REGULATION SHOES

Black, plain toe, conservatively designed. No buckles.

MTA CAP

The Departmental patch shall be sewn on the center front of the cap. The cap shall be worn in the bill forward position and be worn/maintained in a manner so as not to bring discredit to the uniform.

Material

100% Polyester, seamless front baseball cap style with mesh back or cloth back. Round top with adjustable head size. Shall favorably compare with Hanes cap.

Color

Solid black

MEDICAL INSIGNIA

MTA's shall affix the medical caduceus insignia patch or medical caduceus pin above the nametag; the nametag is specified in DOM Section 33020.12.4. The medical caduceus pin shall be gold colored and $\frac{3}{4}$ inch (not to exceed one inch).

Senior MTA's shall affix a medical caduceus pin $\frac{1}{2}$ inch and parallel from the inner edge of the left collar. The chevrons as specified in DOM Section 33020.12.6 shall be worn $\frac{1}{2}$ inch and parallel from the inner edge of the right collar. The bottom edge of the insignia shall be 1 inch from the collar point.

SERVICE STRIPES [Optional]

One service stripe shall be worn for each three years of service as a MTA. Shall be worn $\frac{3}{4}$ inches above the cuff on the left sleeve of the long sleeve regulation shirt.

Color

Gold thread sewn to a black felt material background with a heat-seal treatment on the back. Sewn on the garment with black thread sewn along the border of the $\frac{3}{8}$ -inch by 2 inches stripe.

NAMEPLATE

Departmental name plate; white letters on black plate; refer to DOM section 33020.12.4

DEPARTMENTAL SHOULDER PATCH

Refer to DOM section 33020.12.3

PERSONAL GROOMING

Refer to DOM section 33020.6

MTA MATERNITY UNIFORM

Same as DOM 33020.8.2; Refer to maternity uniforms, page 70 of this handbook

ACCESSORIES

- Whistle - Gold in color
- Belt - Black, solid in color

REGULATION UNIFORM – FOOD SERVICES EMPLOYEES

All supervising cooks, bakers, butcher/meat cutters, and food services workers shall wear the departmentally approved uniform to distinguish them from inmates assigned to food services duties. The uniform shall consist of the following items:

- Shirts: tan, equivalent to Big Mac or Levi's with 3 inch CDC patch over the left breast pocket.
- Trousers: dark brown, equivalent to Big Mac or Levi's.
- Shoes: must be non-skid brown/black, leather uppers only, plain toe conservatively designed. No buckles or designs on or in leather of any sort. Leather must be of smooth texture. Heels not to exceed 1 ½ inches in height. Soles must be non-skid type and oil resistant. Military style shoes are acceptable, no cowboy boots or tennis/gym type shoes.
- Caps: solid brown, baseball type, to match clothing, with 3 inch CDC patch and the employee classification rocker arm above/atop the patch.
- Jackets: brown in color, with 3 inch CDC patch on the left breast.
- Jumpsuit: long/short sleeve solid brown in color.
- Smock: tan in color.

The following items are mandatory accessories:

- Belt, brown/black in color
- Key ring holder
- Whistle
- Name tag

The following items are non-mandatory accessories:

- Alarm holder
- Flashlight

Food service employees shall report to their assignment in clean uniforms that are in good condition.

PROTECTIVE VESTS

The protective vest is a departmentally tested and approved item of safety equipment designed and manufactured to defeat penetration of knives, ice picks and other sharp objects thrust at the wearer.

MANDATORY WEAR

Protective vests shall be worn by all staff members temporarily or permanently assigned to a Security Housing Unit (SHU), Administrative Segregation Unit (Ad-Seg), or Psychiatric Services Unit (PSU) when the staff members are:

- In the vicinity of inmates within the aforementioned units (unrestrained and/or restrained).
- Escorting inmates housed within the aforementioned units anywhere on institution grounds.
- On the aforementioned unit tiers.

These protective vest mandatory wear provisions shall extend to all official visitors of the aforementioned units.

This notice shall be conveyed by a departmentally approved sign posted conspicuously near the entrance of each noted unit.

At the discretion of the Warden, and upon approval of the respective Regional Administrator, the protective vest mandatory wear provision may extend beyond the scope of SHU, Ad-Seg, and PSU Units, if deemed necessary for staff/visitor safety.

EXEMPTIONS

The following are exempt from mandatory vest wear:

- Designated staff assigned to gun posts or isolated cage positions, which preclude any contact with lockup inmates only while actually at such posts.

ENVIRONMENT

Environmental factors such as heat, cold, humidity; etc. shall not void the requirements to wear protective vests.

METHOD OF WEAR

Protective vest shall be worn only in the manner prescribed by the manufacturer and the departmental training guidelines. Protective vests shall not be worn in any manner, which might reduce their designed level of effectiveness.

PROCUREMENT

Each institution shall purchase protective vests directly from the contracted vendor as designated by the CDC Emergency Operations Unit (EOU). Institutions shall ensure that an appropriate quantity and size selection is available for utilization, inclusive of a standby/replacement pool. Institutions shall adhere to policy and procedure governing the purchase/procurement of equipment.

ACCOUNTABILITY AND REPLACEMENT

The procedures for accountability, and replacement of the protective vests are as follows:

ACCOUNTABILITY:

Each warden shall appoint a Property Control Officer (PCO) who shall accept, inventory, and return (as necessary) the facility's protective vests. The PCO shall provide reports of inventory discrepancies or other requested information relative to protective vests directly to the Chief Deputy Warden, who is responsible for the accountability of the institution's protective vests.

REPLACEMENT:

Replacement of the protective vests inserts and covers shall be accomplished as follows:

- Items determined to be unserviceable due to normal wear shall be documented in the institution's monthly PCO inventory report with the following information:
 - Serial number of vest inserts.
 - Date placed into service.
 - Unit in which used.
 - Type of damage sustained.
- Items determined to be unserviceable due to damage beyond normal wear, but not due to negligence shall be documented in the institution's monthly PCO inventory report with the following information:
 - Serial number of vest inserts.
 - Date placed into service.
 - Unit in which used.
 - Type of damage sustained.
 - Brief description of circumstance and corrective action, if any.
- Items determined to be unserviceable due to negligence, intentional destruction, or loss will be reported by the next day of business to the Chief Deputy Warden with the information required above, plus a copy of any documentation regarding progressive discipline and/or adverse action.

INVENTORIES

Each institution shall establish procedures to provide their respective Chief Deputy Warden a monthly inventory of its protective vests. Institutions shall submit to the Emergency Operations Unit a quarterly protective vest inventory by the 15th of the month following each quarter. The CDC Form 1405, Protective Vest Quarterly Inventory Summary (Exhibit "C") shall be completed.

Protective vests which are secured, as evidence shall be documented in the institution's monthly PCO inventory report with the following information:

- Serial number of vest inserts.
- Date and time of incident.
- Nature of incident.
- Nature of any injuries to the person wearing the vest.
- Weapons used, if any.
- Damage to vest, if any.
- Location of evidence storage area.

TRAINING

Standardized training shall be provided to all lockup unit employees, and shall address the following concerns:

- The care and maintenance of the vest.
- The proper manner of wear to ensure maximum protection.
- Should training setting and accommodations allow a confidential demonstration of the protective capabilities and deficiencies of the vest may be conducted.
- Wearer demeanor.
- Departmental/institutional expectations relative to prescribed wearing conditions.

- Departmental expectations and supervisory responsibilities relative to mandatory-wear assignments.

In-service training shall be mandatory for all supervisory lockup unit personnel. Line employees may attend In-service training, but will normally receive required On the Job Training (OJT) instruction from their supervisors.

CERTIFICATION

Each employee required to wear a protective vest shall receive the above training. Institutional training officers shall establish appropriate documentation reflecting course certification. Such record of certification shall be retained in the employee's training file.

LOCAL OPERATIONAL PROCEDURES

Each institution shall establish and review annually a local operational procedure, which shall include, but not be limited to:

- Designating a property control officer by position title and number.
- Procedures for conducting monthly and quarterly inventories.
- Mandatory wear provisions.
- Identified secured storage areas to which no inmates have access.
- Provisions to ensure inmates shall never be allowed to handle protective inserts.
- Check in/check out procedures.
- Procedures for replacement of and procuring additional vests as required.

CLEANING AND CARE:

The procedure shall include:

- Detailed schedule for cleaning.
- Designation of an employee, by duty assignment, to be responsible for the cleaning and maintenance of protective vest components.
- Provisions to ensure that protective inserts are cleaned:

- In the designated storage area.
- Not less frequently than weekly.
- By wiping with a damp cloth or as directed by vendor maintenance labels.
- Provisions to ensure a critical visual inspection of each insert cleaned to ascertain continued integrity of the nylon covering, stitching and wearability.
- Provisions to ensure repair/replacement procedures are initiated immediately when protective inserts show evidence of damage or excessive wear.
- The specific methods utilized to ensure that vest covers (outer garment) are regularly dry cleaned to fulfill the personal hygiene needs of all employees.
- Actions to be taken to ensure timely cleaning in the event of a lock down and/or dry cleaning equipment failure.
- Adequate security precautions to ensure the continued functional capability of each vest cover to perform as a carrier for protective inserts.

REFUSAL TO WEAR

Any employee whose assignment mandates the wearing of a protective vest and then refuses to wear the vest in the manner prescribed by the manufacturer's specifications and departmental training guidelines shall be subject to progressive discipline and/or adverse action. The employee shall be reassigned to a non-mandatory wear assignment pending disposition of the progressive discipline and/or adverse action.

REVISIONS

The Deputy Director, Institutions Division, or designee shall ensure that the content of this section is accurate and current.

REFERENCES

Penal Code Sections 830.2 (f), 830.31(a), 830.5(b), and 830.10.
 California Code of Regulations, Title 2, Section 599.726 et seq.
 California Code of Regulations, Title 15, Division 3, Sections 3291(b) and 3393.